

- STATE "SS" #1, 12,270 TD.
7/10 Hold for compl.
- STATE "SS" #1, 12,270 TD.
7/11 Hold for compl.
- STATE "SS" #1, 12,270 TD.
7/12 Prep to compl.
- STATE "SS" #1, 12,270 TD.
7/13 MIRU X-Pert Well Serv unit 7/12/74, inst'l wellhead & BOP, ran 6-1/8 bit 7" csg scraper on 2 - 4 1/4 DC's and 103 jts 2-3/8 tbg, SDFN.
- 7/15 Finish running bit to 5273, displ mud w/ wtr, drill cmt 5273-78, ran bit to 11,870 top of cmt, displ hole w/ wtr, SDFN & Sunday.
- STATE "SS" #1, 12,270 TD.
7/16 Drill cmt from 11,870-12,200 PB, circ clean, test csg 2000#/ok, displ hole w/ CaCl wtr, SDFN.
- STATE "SS" #1, 12,270 TD.
7/17 POH w/ tbg, DC's and bit, Wellex ran GR-Collar-Corr log from 9900-10,150 & 11,050-12,204, then perf 7" liner in the Morrow @ 12,082-12,091 w/ 2 JSPF, total 20 holes, then set Baker 7" Model D pkr @ 12,054, now running 2-3/8 tbg, seal assembly, ER recpt, 112 jts in hole, testing to 5000# while running, SDFN.
- STATE "SS" #1, 12,270 TD.
7/18 Finish running 2-3/8" tbg to 12,073, F nipple w/1.81 ID @ 12,064 Baker latch in seal assembly @ 12,054, Baker ER receptacle @ 12,039, total 387 jts 2-3/8" EUE 8rd N-80 tbg, unlatch from receptacle, displace hole w/ 9.5# TSW, latch back onto rec, remove BOP, land tbg w/12,000# tension inst tree, SD for nite.
- STATE "SS" #1, 12,270 TD.
7/19 SI 10-1/2 hrs, TP 100#, bled off pressure, sw tbg dry from surface to 9500', sl sh of gas, SI 13 hrs, TP 50#, prep to acidize w/2500 gals acid.
- STATE "SS" #1, 12,270 TD.
7/20 Ran sw, 3000' FIH, Sw tbg dry to 11,000/7 hrs, sl sh of gas, Dowell acidize Morrow perfs 12,082-12,091 w/2500 gals 7 1/2% Easy flow acid, used 30 RCNBS, flushed w/ 30 bbls KCL wtr, all fluid contained 1000 SCF N2/bbl, BDTP 3000, TTP 7000-7700, AIR 7.5 BPM, ISIP 5300, 5 min 3500, job compl 5 pm 7/19/74, fl to pits 1 hr, died, ran sw, 10,000' FIH, sw tbg dry to 8500, cont to sw test w/ sl sh of gas.
- 7/22 Sw tbg dry to 11,500, making small amt of gas, TSTM, L hr sw 1 bbl LW, SI 29 hrs, TP 700.
- STATE "SS" #1, 12,270 TD.
7/23 Bled off press, ran sw, FL @ 7500, sw dry, making small amt of gas, SI 13 hrs, TP 250.
- STATE "SS" #1, 12,270 TD.
7/24 Bled off press, ran sw, 3000' FIH, load tbg w/ 9.5# SW, rel seal assembly from Baker Model D pkr @ 12,054, POH w/ 2-3/8 tbg, recpt & seal assembly, ran Baker DR plug on 2-3/8 tbg, latched into pkr @ 12,054, test plug 2000#/ok, displ hole w/ CaCl wtr, SDFN.