

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
JUL 17 1974
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L K-4101
7. Unit Agreement Name
8. Farm or Lease Name SOUTH ROCK TANK
9. Well No. 1
10. Field and Pool, or Wildcat WILDCAT
12. County EDDY

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRILLING
2. Name of Operator Amoco Production Company
3. Address of Operator BOX 68, HOBBS, N. M. 88240
4. Location of Well UNIT LETTER #5 1980 FEET FROM THE NORTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 2 TOWNSHIP 24-S RANGE 24-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3966 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

OPERATOR changed from: Midwest Oil Corp.
On 6/15/74, 13 3/8" OD 48" Casing was set @ 402' w/ 300 sx class C + additives. Did not circ. (BJ Pump Ser) Filled outside of Cg to surface w/ redymix. Rdy w/ Spudder. WOC.
Drilled out of shoe w/ 18" spudder hole to a TD of 441.
Moved in Rotary tools (Noble Drly Corp) Beamed hole to 12 1/4" and resumed drilling @ 441.
Will drill to TD w/ rotary.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Loy R. Rybakum	TITLE ADMINISTRATIVE ASSISTANT	DATE JUL 16 1974
APPROVED BY W. A. Gussett	TITLE OIL AND GAS INSPECTOR	DATE JUL 18 1974

042. NMOC-C-A-1
 1-DIV
 APPROVED BY
 1-8057
 CONDITIONS OF APPROVAL, IF ANY:
 1-RRY