

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-027994-A

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

S. Carlsbad Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

25-T23S-R26E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

J.M. Huber Corporation

3. ADDRESS OF OPERATOR

1900 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

1900' FNSWL Section 25-T23S-R26E
Eddy County, New Mexico

14. PERMIT NO.

Blanket

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3226.7' CR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. Pool Well Service, cut off 9-5/8" intermediate casing at free point (top of cement at 1150' by temperature survey) and pull 9-5/8" casing. Run 2-3/8" EUE tubing and spot 55 sack Class "H" cement plug (100') 50' in and 50' out of 9-5/8" casing stub. Spot 75 sack Class "H" cement plug through 2-3/8" tubing across 13-3/8" surface shoe, from 546' - 646' (13-3/8" casing shoe @ 596'). Spot 10 sack surface plug, weld on plate and install 4" DH marker. Cement service to be done by B.J.

Procedure approved by Mr. Jim Knauf by telephone 10-29-74.

RECEIVED

OCT 30 1974
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

James R. Sutherland

TITLE District Prod. Mgr.

DATE 10-29-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE