## "ED STATES DEPARTML. TOF THE INTERIOR (Other interior verse side)

SUBMIT IN TRI

approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO.

NM 0544986 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL SURVEY						
SUNDRY	NOTICES	AND	REPORTS	ON	WELLS	

	(Do not use this form for proposals to drill or to deepen or Use "APPLICATION FOR PEHMIT—" for			
ī.	OIL GAS X OTHER	RECEIVED	7. UNIT AGREEMENT NA	M B
2.	2. NAME OF OPERATOR	( ) ( ) ( ) ( )	8. FARM OR LEASE NAM	
	Texas American Oil Corporation	JUL 2 5 1974	Todd ''25''	<u>Federal</u>
3.	3. ADDRESS OF OPERATOR		9. WELL NO.	
	1012 Midland Savings Bldg., Midla	1-Z		
4.	4. LOCATION OF WELL (Report location clearly and in accordance with See also space 17 below.) At surface	Wildeat	R WILDCAT	
	1980' FNL & 1970' FWL		11. sec., T., R., M., OR E SURVEY OR ABEA  Sec. 25, T-2	
14	14. PERMIT NO.   15. ELEVATIONS (Show whe	ether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
	3486.7 G	\$R	Eddy	New Mexico
16	16. Check Appropriate Box To India	rate Nature of Notice, Report, or C	ther Data	•

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF REPAIRING WELL		
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT  SHOOTING OR ACIDIZING  ABANDONMENT*		
SHOOT OR ACIDIZE		ABANDON*		Sacorard on assessment		
REPAIR WELL		CHANGE PLANS		(Other)(Nort: Report results of multiple completion on Well		
(Other)			<u> </u>	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

## 4-16-74 to 7-14-74:

Drilled 24" hole to 600' with Cable Tools. Ran 20" - 94# H-40 surface casing and set at 600'. Cemented with 600 sxs Class "C" with 4% gel & 2% CaCl and 1/4# celloflakes/sx., followed with 200 sxs Class "C" with 2% CaCl. Spotted 100 sxs down 1" pipe to complete cement job.

	•				
18. I hereb certify that the foregoing is true and correct SIGNED	TITLE _	Production Superintendent DATE	July	16,	1974
(This space for Federal or State office use)  APPROVED BY  CONDITIONS OF APPROVAL IF ANY:	TITLE _	DATE _	-		

\*See Instructions on Reverse Side