

COPIES RECEIVED	22
TRIBUTION	
FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 15 1974

O. C. C.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	-----	
7. Unit Agreement Name	-----	
8. Farm or Lease Name	Cedar Canyon 9-D	
9. Well No.	1	
10. Field and Pool, or Wildcat	Wildcat	
12. County	Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-

2. Name of Operator
Skelly Oil Company

3. Address of Operator
P. O. Box 1351, Midland, Texas 79701

4. Location of Well
UNIT LETTER **0**, **1980** FEET FROM THE **East** LINE AND **660** FEET FROM THE **South** LINE, SECTION **9** TOWNSHIP **24S** RANGE **29E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
2930.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Spud and set 8-5/8" OD casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Spudded 11" OD hole at 7:00 p.m. 8-1-74.
- 2) Drilled to 400'
- 3) Set 11 joints (383') 8-5/8" OD casing at 399'.
- 4) Cemented with 200 sacks Class "C" cement with 2% CaCl. Cement failed to circulate. Cemented to top with 115 sacks Class "C" cement neat. WOC 24 hours.
- 5) Tested 8-5/8" OD casing to 500#. Held okay.
- 6) Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED (Signed) J. R. Avent **J. R. Avent** TITLE Dist. Admin. Coordinator DATE 8-13-74

APPROVED BY W. A. Gussert TITLE OIL AND GAS INSPECTOR DATE AUG 21 1974

CONDITIONS OF APPROVAL, IF ANY: