

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIP!  
(Other instructions  
verse side)

TE  
re-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0556916

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Franklin, Aston & Fair, Inc. ✓

3. ADDRESS OF OPERATOR

P.O. Box 1090 Roswell, New Mexico

DEC 6 1974

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface 1700' FNL & 2180' FEL,  
Section 31-24S-22E, N.M.P.M.  
(SW $\frac{1}{4}$ NE $\frac{1}{4}$ )

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

Turkey Draw Unit

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 31-24S-22E, NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5828.3 GL

12. COUNTY OR PARISH

13. STATE

Eddy County

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Set 8-5/8" intermediate csg.

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On November 26, 1974, 8-5/8", 32#, casing was set at 2200' KB with 740 sacks Halliburton lite cement, 5# gilsonite,  $\frac{1}{4}$ # flocele per sack and 2% CaCl followed by 150 sacks Class "C" cement, 2% CaCl. The cement did not circulate. Temperature survey indicated top of cement at 1290'. A 1" macaroni string was run down back side and tagged cement at 1207'. The cement was brought to surface in 15 stages using 725 sacks cement. All cementing work done by Halliburton.

RECEIVED

DEC - 4 1974

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Grant M. Smith*

TITLE

Geologist

DATE

12-2-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

DEC 5 - 1974

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side