

N. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

DEC 10 1974

Form O-103
Supersedes Old
C-102 and C-103
Effective 1-1-68

SUNDY NOTICES AND REPORTS ON WELLS C. C. DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH ARTESIAN OFFICE		5a. Indicate Type of Lease State <input type="checkbox"/> - Fee <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.		
7. Unit Agreement Name		
8. Name of Lease Owner Donnelly		
9. Well No. 1		
10. Field and Pool, or Wildcat Wildcat Morrow		
11. Elevation (Show whether DF, RT, GR, etc.) G.L. 3047'		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled an 11" hole to 3020'. Ran 79 jts 8 5/8" 24# & 32# J55 8rd STC casing, set at 3028'. Cemented with 1000 sacks Lite Wate followed by 200 sacks Class C with 2% CaCl₂, 1/4# Flocele/sack in all cement. Pumped plug down with 188.5 barrels fresh water at 1:45 a.m., 11-24-74. Cement did not circulate. Top of cement via temperature survey at 500'. Ran 1" to 480'. Cemented with 450 sacks Class C at 12:15 p.m., 11-24-74. Cement circulated. WOC 18 hrs. Tested casing to 1000 psi. Held OK. Drilled out with 7 7/8" hole. This a.m., drilling at 7275' with no problems.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. C. Radtke (D. C. Radtke) TITLE Engineer DATE 12-5-74

APPROVED BY W. A. Grunert TITLE OIL AND GAS INSPECTOR DATE DEC 10 1974
CONDITIONS OF APPROVAL, IF ANY: