

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 23 1975

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> <input type="checkbox"/>	F-# <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-4542	

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	6. C. C. C. ARTESIA, OFFICE	7. Unit Agreement Name
2. Name of Operator Corinne Grace ✓		8. Firm or Lease Name Sulphate Uncle
3. Address of Operator P. O. Box 1413, Carlsbad, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 24S RANGE 27E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, CR, etc.) 3204.6		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 18, 1975

Ran 638' of 13 3/8" 54# casing and cemented with 400 sk Halliburton Lt. wt w/4# of Gilsonite & 1/4# of floccel per bbl. slurry wt. 13.2 Followed w/200 sks Class "C" neat displaced plug to 620' w/no cmt. returns WOC 4 hrs. Ran 1 1/4" tbg. in 13 3/8 by 18" annulus tagged cement at 370'. Pumped 50 sk lite wt. cement slurry wt. 13.2 thru tbg. WOC 3 hr. & tagged cement at 270'. Mixed & Pumped thru tbg. 150 sk lite wt. cement w/4# of gilsonite & 2% cal cl. slurry wt. 13.2 Got cement returns to surface. WOC 24 hrs. Will pressure up before drilling out.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Corinne Grace

TITLE Agent

DATE 6/19/75

APPROVED BY W. A. Grissett
CONDITIONS OF APPROVAL, IF ANY:

TITLE SUPERVISOR, DISTRICT II

DATE JUN 23 1975