

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>AMERICAN QUASAR PETROLEUM Co</u>		Lease <u>HUBER STATE</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>36</u>	Township <u>23-S</u>	Range <u>22-E</u>	County <u>EDDY</u>
Drilling Contractor	<u>ARD RIG #7</u>		Type of Equipment <u>ROTARY</u>		

APPROVED CASING PROGRAM APPROVED 12-20-74

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>30"</u>	<u>20"</u>	<u>78.6</u>		<u>50'</u>	<u>READY-MIX</u>
<u>17 1/2</u>	<u>13 3/8"</u>	<u>48</u>		<u>400</u>	<u>350 SX - CIRC</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>24 3/32 #</u>		<u>2500</u>	<u>1150 SX - CIRC</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17 #</u>		<u>10500'</u>	<u>400 SX</u>

Casing Data:

INTER 56 joints of 8 5/8 inch 24 3/32 # Grade K-55
OK (Approved) (Rejected)

Inspected by Sam Bergstrom date 1-10-75

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 1150

Type of Shoe used GUIDE Float collar used INSERT Btm 3 jts welded THREAD-LOK

TD of hole 2479 KB Set 2463 GL Feet of 8 5/8 Inch 24 3/32 # Grade K-55

New-~~cas~~ csg. @ 2463 GL with 200 sacks neat cement around shoe
+ 950 sax TOP OF 8 5/8 additives 950 SX w/ 5 # GILS/SX & 1/4 # FLOCELE
200 SX w/ 2 # CA CL2 CLASS C " AROUND SHOE

Plug down @ 3 30 (AM) (PM) Date 1-10-75

Cement circulated YES No. of Sacks 50-60 BBLs CMT CIRC. TO PIT

Cemented by HALLIBURTON Witnessed by Sam Bergstrom

Temp. Survey ran @ (AM) (PM) Date top cement @ SURFACE

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: