

SUBSURFACE EQUIPMENT INSTALLATION REPORT

FIELD: Wild Cat

COUNTY: Eddy, New Mexico

WELL:43

TOTAL DEPTH: 31.5'

DATE OF INSTALLATION: 3-27-75

REASON FOR INSTALLATION: New well

TIME REQUIRED: UNIT NO.

HOURS. OPERATOR

HOURS. CREW

MAN-HOURS.

DEPTHS ARE SHOWN FROM: Kelly Drive Bushings

No. of Joints	DESCRIPTION	THDS. OFF LENGTH	FROM	TO
7	Rotary Correction. 13-3/8" O.D. 48 #/ft H-40-stac casing.	21.00	0.00	21.00
	Howco Float Collar	248.83	21.00	269.83
1	13-3/8" O.D. 48 #/ft H-40-stac casing.	1.50	269.83	271.33
	Howco down jet shoe.	40.20	271.33	311.53
		1.80	311.53	313.33
	Btm. 2 jts & float equipt. Howco - sealed & welded 3 Howco spring type centralizers on btm. 3 jts.			
	Howco cemented w/400 sk. class "C" containing 2% CaCl and 1/4#/sk flocele			
	Circulated out 120 sks. slurry wt. 8 PPG.			
	Pump plug with 500 psi -- held ok.			
	Plug down @ 2:45 p.m.			
	Jt. cut off 32.10			

RECEIVED
APR 10 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED
APR 10 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

DATE: