

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0415688-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

DISPOSAL WELL MAY 4 1976

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

P.O. DRAWER A, LEVELLAND, TEXAS, 79336

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL x 660' FEL SEC. 18 (UNIT I, NE/4 SE/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3086. GL

7. UNIT AGREEMENT NAME

OLD INDIAN DRAW UNIT

8. FARM OR LEASE NAME

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

INDIAN DRAW-DELAWARE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18-22-28 NMPM

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

CONVERSION TO SWD Disp.
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

WORKOVER TO CONVERT TO SWD. SQUEEZED PERFS. 2476-2501', 3316-26 w/ 250 sx Class "C" Cement + Additives w/ 2000 PSI. REV. out 2 sx. Drilled out to 3411'. Perf. INTERVALS 3376-3400' w/ 2 JSPP. Acidize w/ 2580 gals. 15% N.E. 2 3/8" OD 4.7 # J-55 Plastic Coated tubing landed and Packer set @ 3358'. Installed pressure gauge on casing-tubing annulus. Well completed 4/29/76 and ready for disposal. TD-3463' PBD 3/27/76

RECEIVED
MAY - 3 1976
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

SWD APPROVAL BY NMOCC

2/24/76.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray W. Cop

TITLE

ADMINISTRATIVE ASSISTANT

DATE

4/30/76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

014. USGS-ARF

1- Div
1- Sup.
1- RC
1- Perry Bass
1- Marathas