

C15F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a plugback to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other Injection **JUL 31 1980**

2. NAME OF OPERATOR
Amoco Production Company **U.S. GEOLOGICAL SURVEY**

3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240 **ARTESIA, NEW MEXICO**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL X 660' FEL, Sec. 18
AT TOP PROD. INTERVAL: (Unit I, NE/4, SE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) _____

5. LEASE
NM-0415688-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Old Indian Draw Unit Fed.

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Indian Draw-Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
18-22-28

12. COUNTY OR PARISH | 13. STATE
Eddy | NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3086' FL

RECEIVED
AUG 1 1980
O. C. D.
ARTESIA, OFFICE

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to convert salt water disposal to pilot injector for waterflood by the following method:

Pull packer and run 2-3/8" workstring and cement. Set retainer at 3360'. Squeeze SWD zone 3376'-3400' with 100 sacks of Class 'C' cement. Circulate out excess cement. Pull tubing. Perforate Delaware interval 3316'-44' with 4 JSPF. Run tubing and packer. Set packer at 3285'. Acidize interval with 1000 gallons 7-1/2% clay stailizing acid. Flush with 15 bbls. fresh water. Run plastic coated pipe and packer. Set packer at 3285'. Place well on injection.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct
SIGNED Marilyn Kots TITLE Ast. Ad. Analyst DATE 7-30-80

(This space for Federal or State office use)
APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEER DATE JUL 31 1980

CONDITIONS OF APPROVAL, IF ANY:
0+4-USGS, A 1-Hou 1-Susp 1-MKE
Subject to concurrence by N.M.O.C.D.