

© Copyrighted Reproduction Prohibited

EDDY Wildcat NM

C & K PETROLEUM, INC. 30-015-21605

1 LEASE Allied Chemical Federal 1-5-11 NM

Sec 4, T-24-S, R-26-E

1980' FNL, 990' FWL of Sec

4 1/2 mi NW/Black River

8-13-75 1-1-76

WEL. CLASS: INT. WF FIN WED

FORMATION DATUM FORMATION DATUM

TD 12,070' (BRNT) PSD 1900'

IP (Delaware) Perfs 1680-90' P 14 BOPD + 105 BW. Pot based on 24 hr test. GOR 100; Grav 37

CONTR Sharp OPR'S ELEV 3419' GL PD 12,000' RT

F.R. 8-18-75
(Morrow)

8-19-75 TD 1922'; On DST 1860-1922

8-26-75 TD 4649' lm, sd & sh; Trip
DST (Delaware) 1860-1922', open 1 hr 30 mins,
rec 400' DF w/sli show oil, 1 hr ISIP 661#, FP
93-159#, 3 hr FSIP 661#, HP 818-818#, BHT 92 deg

9-2-75 Drlg 6005'

9-9-75 Drlg 8598' lm & sh

9-16-75 Drlg 10,424' sh & lm

9-23-75 Drlg 10,820' lm & sh
DST (Strawn) 10,460-652', open 1 hr 30 mins,
rec 6500' GDP, 1 hr 30 min ISIP 509#, FP 162-
162#, 2 hr FSIP 787#, HP 5320-4931#, BHT 107 deg

1-5-11 NM

EDDY

C & K PETROLEUM, INC.

Wildcat

NM

1 Allied Chemical Federal Page #2
Sec 4, T24S, R26E

9-30-75

Drlg 11,571' 1m & sh

10-7-75

Drlg 11,990' 1m & sh

DST (Morrow) 11,546-682', open 2 hrs, rev
out GCDF (Sampler rec 2400 cc's FW w/trace
gas @ less than 150#), 1 hr 30 min ISIP 4809#,
FP 162-462#, 3 hr FSIP 4672#, HP 6130-6107#
DST (Morrow) 11,546-790', open 2 hrs, rec 500'
GCM + 485' GCSW, 1 hr 30 min ISIP 4935#, FP
429-644#, 4 hr FSIP 4788#, HP 6285-6285#, BHT
195 deg

10-13-75

TD 12,070'; WOO

10-21-75

TD 12,070'; PBD 5350'; WOCU

Erroneously reported D&A on 10-13-75

PB to 5350'

1-5-11 NM

10-28-75

TD 12,070'; PBD 5350'; MICU

11-4-75

TD 12,070'; PBD 5046'; Swbg

Perf (Delaware) 5292-98' w/1 SPF

Acid (5292-98') 500 gals

Swbd Non-Productive (5292-98')

Perf (Delaware) 5170-78' w/2 SPF

Swbd dry (5170-78')

Perf (Delaware) 5108-14' w/2 SPF

Acid (5108-14') 450 gals

Swbd dry (5108-14')

BP @ 5046'

Perf (Delaware) 4972-84' w/2 SPF

Acid (4972-84') 350 gals

11-11-75

TD 12,070'; PBD 5046'; Swbg

Swbd 18 BW & Swbd Dry (4972-84')

Perf (Delaware) 1680-90' w/2 SPF

Acid (1680-90') 350 gals

Swbd 36 BO + 9 BW (1680-90')

1-5-11 NM