

5. LOCATION AND TYPE OF WATER SUPPLY:

- A. It is planned to drill the plugged well with fresh water that will be obtained from private or commercial sources and will be transported over the existing and proposed access roads.

6. SOURCE OF CONSTRUCTION MATERIALS:

- A. If needed or required caliche for repairing the existing access road and well site pad will be obtained from the location, with a backup approved Federal pit in NE $\frac{1}{4}$ -Sec. 4-T24S-R26E. No surface materials will be disturbed except those necessary for actual grading and repairing of the drill site and access road.

7. METHODS OF HANDLING WASTE DISPOSAL:

- A. Drill cuttings will be disposed of in the working pit.
- B. Drilling fluids will be allowed to evaporate in the working pit until the pits are dry.
- C. All pits will be fenced with normal fencing materials to prevent livestock from entering the area.
- D. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or a separate disposal application will be submitted to the BLM for approval.
- E. Oil produced during operations will be stored in tanks until sold.
- F. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- G. Trash, waste paper, garbage and junk will be contained in trash bins to prevent scattering and will be removed for deposit in an approved sanitary land fill within 30 days after finishing drilling and/or completion operations.

8. ANCILLARY FACILITIES:

- A. None required.

9. WELL SITE LAYOUT:

- A. Exhibit "D" shows the relative location and dimensions of the well pad, working pit, and major rig components. The well pad and pit area will be confined to the existing disturbed area of the old location.
- B. Mat Size: 150' X 150', including mud pit.
- C. Cut & Fill: None required.
- D. The surface will be topped with the compacted caliche that is presently on the pad and additional caliche will be added if needed. The pit will be plastic lined.