			-		<u> </u>
				NM OIL COL	as commission 5</td
				Drawer DD	
				Artesia,	NM 88210
- 2160 5	LINIT	ED STATES			M APPROVED
rm 3160-5 ne 1990)			D		reau No. 1004-0135
uc (770)		DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			: March 31, 1993 ation and Serial No.
	BUREAU OF 1.	AND MANAGEME			
	SUNDRY NOTICES	AND REPORTS OF	WELLS UPFAIL OF	NM-9	US14 ottee or Tribe Name
Do not use this for	rm for proposals to dri	ll or to deepen of re	entry to a different reservo	i .	ouee of the name
	se "APPLICATION FOR	PERMIT-" for suc	ch proposals	X	
				TR 7 If Unit or C	Agreement Designation
	SUBMIT	IN TRIPLICATE	1 · · · · · · · · · · · · · · · · · · ·		, reforment beitgindon
Type of Well	······································				
Great Oil Cas			17. °A 89.	8. Well Name an	id No.
Well Well Name of Operator	L_] Other			ASPEN F	EDERAL #1
SNOW OIL & G	GAS. INC.	V	1. M.	9. API Well No.	
Address and Telephone N			South and Co	30-015-	21605
P.O. BOX 127		, TEXAS 79714	(915) 524-2371		ol, or Exploratory Area
	e, Sec., T., R., M., or Survey De				(DELAWARE)
	-,,,,,,	· · · · · · · · · · · · · · · · · · ·		11. County or P	
1980' FNL &	990' FWL See	ction 4, T24S,	R26E		
			LE	EDDY CC	UNTY, NEW MEXICO
		U/M_1 7			
CHECK A	APPROPRIATE BOX	s) TO INDICATE N	ATURE OF NOTICE, REI		
TYPE OF S	SUBMISSION	TYPE OF ACTION			
Notice of Intent				Change o	f Plans
					ine Fracturing
IY Cuberry	X Subsequent Report		nging Back	i Non-Rout	
KLI Subseque	chi Kepon		gging Back		- w-Off
-			ing Repair	Water Sh	
-	andonment Notice	Cas	ing Repair ering Casing	Water Sh	on to Injection
-			ing Repair ering Casing	Water Sh Conversion Dispose (Note: Report re	on to Injection Water sults of multiple completion on Well
Final Ab	bandonment Notice	Cas Alu Out	ing Repair ering Casing er	Water Sh Conversion Dispose (Note: Report re Completion or R	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form)
Final Ab	mpleted Operations (Clearly state 4	Cas Alu Oth	ing Repair ering Casing er rtinent dates, including estimated date of s	Water Sh Conversion Dispose (Note: Report re Completion or R	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form)
Final Ab B Describe Proposed or Cor give subsurface loca 1/93	mpleted Operations (Clearly state a stions and measured and true verte	Cas Altu Oth Il pertinent details, and give pe cal depths for all markers and 10/11/93	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)*	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled,
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 1fied Carlsbad BLM	mpleted Operations (Clearly state 4	Cas Altu Doth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clean	ing Repair ering Casing er rtinent dates, including estimated date of s	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled,
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 1fied Carlsbad BLM 14/03	mpleted Operations (Clearly state a tions and measured and true vert of of intent to begin open	Il pertinent details, and give per cal depths for all markers and 10/11/93 ations; RUSU, Clean 10/15/93	ing Repair ering Casing ter	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor ridge plugs to 53	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ⁴
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93	mpleted Operations (Clearly state a stions and measured and true vert of of intent to begin open '- 16', 5173'- 76', 5198	Cas Altu Doth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> rations; RUSU, Clean <u>10/15/93</u> 1'- 5200'; Mill tight	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)*	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor ridge plugs to 53	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ⁴
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 1fied Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB	mpleted Operations (Clearly state a tions and measured and true vert of of intent to begin open	Cas Altu Doth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> rations; RUSU, Clean <u>10/15/93</u> 1'- 5200'; Mill tight	ing Repair ering Casing ter	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor ridge plugs to 53	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ⁴
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 8B 19/93	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin open - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> rations; RUSU, Clean <u>10/15/93</u> 1- 5200'; Mill tight dry w/show of gas	ing Repair ering Casing ber	Water Sh Water Sh Conversion Dispose (Note: Report re Completion or R tarting any proposed wor ridge plugs to 53	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ⁴
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB 19/93 c down tubing with 20/03 thmu 10/22/03	mpleted Operations (Clearly state a tions and measured and true verter of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li	Cas Altu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clean <u>10/15/93</u> t'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB 19/93 c down tubing with 20/03 thmu 10/22/03	mpleted Operations (Clearly state a tions and measured and true verter of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li	Cas Altu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clean <u>10/15/93</u> t'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l	ing Repair ering Casing ber	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB 19/93 c down tubing with 20/93 thru 10/22/93 1 flow - various ra (23/93	mpleted Operations (Clearly state a ntions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li 3 ates - flowing tubing pr	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and 10/11/93 ations; RUSU, Clear 10/15/93 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 if 5076'- 80', 5112' 17/93 idized perfs w/10 88 19/93 ic down tubing with 20/93 thru 10/22/93 il flow - various ra 23/93 il well by soft chol	mpleted Operations (Clearly state a tions and measured and true verter of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and 10/11/93 ations; RUSU, Clear 10/15/93 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab Final	mpleted Operations (Clearly state a ntions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li 3 ates - flowing tubing pr	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clean <u>10/15/93</u> t'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests.	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab Final	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atte	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clean <u>10/15/93</u> t'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests.	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M	Water Sh Conversi Note: Reporte Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50 ' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM (14/93 if 5076'- 80', 5112' (17/93 idized perfs w/10 BB (19/93 ic down tubing with /20/93 thru 10/22/93 li flow - various ra (23/93 li well by soft chol 12/94 mp cross link polime 14/94 ut in - waiting on f 5 (04 down d /18()	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pa ke. Shut in pending add er - 2 stages in an atto polimer	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and 10/11/93 ations; RUSU, Clear 10/15/93 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests. empt to reduce water	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M	Water Sh Conversi (Note: Report Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'. 30 BBLS of H20 per
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 8B 19/93 c down tubing with 20/93 thru 10/22/93 1 flow - various ra (23/93 1 well by soft chol 12/94 up cross link polime (4/94 of in - waiting on jac	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pa ke. Shut in pending add er - 2 stages in an atto polimer	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and 10/11/93 ations; RUSU, Clear 10/15/93 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests. empt to reduce water	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M	Water Sh Conversi (Note: Report Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB 19/93 ic down tubing with 20/93 thru 10/22/93 il flow - various ra (23/93 il well by soft chol 22/94 ap cross link polime 15/94 through 4/18/9 ab 180 BBLS of wate 5/94	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atte polimer 94 er in 8 Hrs. Final swat	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clear <u>10/15/93</u> 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests. empt to reduce water report - some gas with	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* In out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le	Water Sh Conversi (Note: Report Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water sults of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 BB 19/93 c down tubing with 20/93 thru 10/22/93 l flow - various ra (23/93) l well by soft chol 12/94 ap cross link polime 14/94 at in - waiting on [15/94 through 4/18/ ab 180 BBLS of wate 5/94 ab well. Starting	mpleted Operations (Clearly state a tions and measured and true vert of of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li <u>3</u> ates - flowing tubing pa ke. Shut in pending add er - 2 stages in an atte polimer <u>94</u> r in 8 Hrs. Final swat fluid level 480', endin	Cas Alu Oth Il pertinent details, and give pe cal depths for all markers and <u>10/11/93</u> ations; RUSU, Clear <u>10/15/93</u> 1'- 5200'; Mill tight dry w/show of gas nk gel and 128,000 l ressure 150 - 200; Es ditional tests. empt to reduce water report - some gas with	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M	Water Sh Conversi (Note: Report Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'.
Final Ab 3 Describe Proposed or Cor give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 8B 19/93 c down tubing with 20/93 thru 10/22/93 l flow - various re (23/93) l well by soft chol 12/94 it in - waiting on f 15/94 through 4/18/9 ab 180 BBLS of wate 5/94 ab well. Starting 10/19	mpleted Operations (Clearly state a stions and measured and true verter of intent to begin oper '- 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li <u>3</u> ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atte polimer <u>94</u> or in 8 Hrs. Final swat fluid level 480', ending	Cas Cas Cas Cas Cas Cas Cas Cas	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)" in out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water.	Water Sh Conversi Note: Reporter Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suks of multiple completion on Wetl ecompletion Report and Log form) k. If well is directionally drilled, 150' and set at 5008'. 30 BBLS of H20 per than 1% oil cut.
Final Ab The second se	mpleted Operations (Clearly state a stions and measured and true vert of of intent to begin oper 2 - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li <u>3</u> ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atto polimer <u>94</u> ar in 8 Hrs. Final swat fluid level 480', endire <u>14</u> orders 2-7/8" Kill stri	Cas Alu Definition of the second se	ing Repair ering Casing er riment dates, including estimated date of s zones pertiment to this work.)" in out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050'	Water Sh Conversi Note: Reporter Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'.
Final Ab The proposed or Cor- give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 8B 19/93 ic down tubing with /20/93 thru 10/22/93 il flow - various ra /23/93 il well by soft chol 12/94 ap cross link polime 14/94 ut in - waiting on 1 15/94 through 4/18// ab 180 BBLS of wate 6/94 ab well. Starting 7/94 through 10/1/9 ut in - waiting on /15/94 ep to submit plaps.	mpleted Operations (Clearly state a titions and measured and true vert of intent to begin oper 9- 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li 3 ates - flowing tubing pa ke. Shut in pending add er - 2 stages in an atte polimer 94 rr in 8 Hrs. Final swat fluid level 480', endin 14 orders 2-7/8" Kill stri for recompletion in Mor	Cas Alu Definition of the second se	ing Repair ering Casing er riment dates, including estimated date of s zones pertiment to this work.)" in out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050'	Water Sh Conversi Note: Reporter Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled. 50' and set at 5008'. 30 BBLS of H20 per than 1% oil cut. TED FOR REC.
Final Ab The proposed or Cor- give subsurface loca 1/93 ified Carlsbad BLM 14/93 f 5076'- 80', 5112' 17/93 dized perfs w/10 8B 19/93 ic down tubing with /20/93 thru 10/22/93 il flow - various ra /23/93 il well by soft chol 12/94 ap cross link polime 14/94 ut in - waiting on 1 15/94 through 4/18// ab 180 BBLS of wate 6/94 ab well. Starting 7/94 through 10/1/9 ut in - waiting on /15/94 ep to submit plaps.	mpleted Operations (Clearly state a stions and measured and true vert of of intent to begin oper 2 - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li <u>3</u> ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atto polimer <u>94</u> ar in 8 Hrs. Final swat fluid level 480', endire <u>14</u> orders 2-7/8" Kill stri	Cas Alu Definition details, and give per cal depths for all markers and 10/11/93 rations; RUSU, Clear 10/15/93 r- 5200'; Mill tight dry w/show of gas ank gel and 128,000 l ressure 150 - 200; Es ditional tests. empt to reduce water report - some gas with g fluid level 900' Re ng at the bottom of from on separate Sund	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 460 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050' ry Notice	Water Sh Conversi Note: Reporter Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'. 30 BBLS of H20 per than 1% oil cut. TED FOR REC.
Final Ab Final	mpleted Operations (Clearly state a titions and measured and true vert of intent to begin oper 9- 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li 3 ates - flowing tubing pa ke. Shut in pending add er - 2 stages in an atte polimer 94 rr in 8 Hrs. Final swat fluid level 480', endin 14 orders 2-7/8" Kill stri for recompletion in Mor	Cas Alu Definition of the second se	ing Repair ering Casing er riment dates, including estimated date of s zones pertiment to this work.)" in out cement and cast iron b spot in 9 5/8" at 422' & 46 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050'	Water Sh Conversi Note: Reporter Completion or R tarting any proposed wor ridge plugs to 53 29', Run packer a ICFPD, 1% oil cut	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled. 50' and set at 5008'. 30 BBLS of H20 per than 1% oil cut. TED FOR REC.
Final Ab The proposed or Corgive subsurface loca 1/93 ified Carlsbad BLM 14/93 dized perfs w/10 BB 19/93 dized perfs w/10 BB 19/93 ic down tubing with 20/93 thru 10/22/93 il well by soft chol 12/94 ab cross link polime 15/94 through 4/18/1 ab well. Starting 7/94 through 10/1/9 ut in - waiting on 15/94 ep to submit plaps 14. 1 hereby certify that the	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atte polimer 94 rr in 8 Hrs. Final swat fluid level 480', endire for recompletion in Mor foregoing forme and correct content of the state of the state of the state for recompletion in Mor	Cas Alu Dertinent details, and give per cal depths for all markers and 10/11/93 ations; RUSU, Clean 10/15/93 ations; RUSU, Clean ation; R	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 460 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050' ry Notice	Water Sh Conversi Conversi Conversi Conjection or R tarting any proposed wor ridge plugs to 53 29', Run packer of CFPD, 1% oil cut evel 3800' - less ACCEF	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 150' and set at 5008'. 30 BBLS of H20 per than 1% oil cut. TED FOR REC 112:27
Final Ab Final	mpleted Operations (Clearly state a stions and measured and true vert of intent to begin oper - 16', 5173'- 76', 5198 BL Acid Pentol 100, swb 33,000 gallons cross li ates - flowing tubing pu ke. Shut in pending add er - 2 stages in an atte polimer 94 rr in 8 Hrs. Final swat fluid level 480', endire for recompletion in Mor foregoing forme and correct content of the state of the state of the state for recompletion in Mor	Cas Alu Definition of the second se	ing Repair ering Casing er rtinent dates, including estimated date of s zones pertinent to this work.)* n out cement and cast iron b spot in 9 5/8" at 422' & 460 bs of 16/30 Ottawa Sand timated gas rate 300 - 700 M flow ith each run. Final fluid le ecover 17 BBLS of water. 1050' ry Notice	Water Sh Conversi Conversi Conversi Conjection or R tarting any proposed wor ridge plugs to 53 29', Run packer of CFPD, 1% oil cut evel 3800' - less ACCEF	on to Injection Water suits of multiple completion on Well ecompletion Report and Log form) k. If well is directionally drilled, 50' and set at 5008'. 30 BBLS of H20 per than 1% oil cut. TED FOR REC.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.