

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
NM 23269

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR MONSANTO COMPANY	8. FARM OR LEASE NAME ROBINIA DRAW
3. ADDRESS OF OPERATOR 321 West Texas, Midland, Texas 79701	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1844' FSL & 2140' FWL	10. FIELD AND POOL, OR WILDCAT WILDCAT
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4020 Gr; 4037 DF
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3, T-23S, R-24E	12. COUNTY OR PARISH Eddy
13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		<input type="checkbox"/>

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		<input type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8 3/4" hole to 10,830'; dry hole; Verbal approval to plug and abandon as follows obtained from Mr. Jim Knauf:

Cement Plugs as follows:

#1	10,400-10,250	150'	55 Sx.
#2	8,975- 8,825	150'	55 Sx.
#3	7,800- 7,650	150'	55 Sx.
#4	5,500- 5,400	100'	40 Sx.
#5	3,650- 3,540	100'	40 Sx.
#6	2,575- 2,425	150'	55 Sx.
#7	20- 0	20'	10 Sx.

Hole between plugs will be filled w/ better than 25% Gel per bbl. wtr.
4" pipe marker w/ location thereon will be set @ surface.

RECEIVED

OCT 24 1975

G. C. C.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Regional Prod. Mgr.

DATE

10/20/75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
NOV 21 1975
G. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side