

1. JWOUT PREVENTER SPECIFICATION  
EQUIPMENT DESCRIPTION

TYPE III-A

All equipment shall be at least 5,000 psi WP or higher unless otherwise specified.

1. Rotating type BOP, 3,000 psi minimum WP.
2. Hydril or Shaffer bag type preventer.
3. Ram type pressure operated preventer with pipe rams. Use large size pipe rams when drilling with a tapered string. Use blind rams when drilling with a tapered string and formation is overbalanced.
4. Flanged spool with two 4-inch side outlets.
5. 4-inch flanged plug or gate valve.
6. 4-inch flanged tee.
7. 4-inch flanged plug or gate valve.
8. 4-inch flanged pressure operated gate valve.
9. Ram type pressure operated preventer with blind rams. Use small size pipe rams when drilling with a tapered drill string.
10. Ram type pressure operated preventer with pipe rams. Use large size pipe rams when drilling with tapered string.
11. Flanged type casing head (furnished by Exxon).
12. 2-inch flanged plug or gate valves (furnished by Exxon).
13. 2-inch threaded flange (furnished by Exxon).
14. 2-inch tapped bull plug (furnished by Exxon).
15. Needle valve (furnished by Exxon).
16. 4-inch flanged spacer spool.
17. 4-inch by 2-inch flanged cross.
18. 2-inch flanged plug or gate valve.
19. 2-inch flanged adjustable choke. Replace with flanged 2-inch tee if a remote controlled choke is installed downstream.
20. 4-inch x 4-inch spacer flange w/1-inch tap.
21. 1-inch x 4-inch XXH nipple.
22. 1-inch valve.
23. Cameron (or equal.) 0-6000 psi gage.
24. 2-inch flanged spacer spool.
25. 6-inch or 4-inch pipe, 300' to pit, anchored.
26. 2-1/2-inch line to separator.
27. 2-inch weld neck flange.
28. 2-1/2-inch x 2-inch sch. 80 concentric weld reducer.
29. 2-1/2-inch pipe.
30. Pressure operated adjustable choke (furnished by Exxon).
31. 2-1/2-inch S.E. gate valve.
32. 2-1/2-inch tee.
33. 2-1/2-inch pipe, 300' to pit, anchored.
34. 2-inch threaded flange (EUE) or weld neck flange w/Weco Fig. 1502 2" 15,000 psi free flow buttress weld wing union.
35. 4-inch flanged tee.
36. 3-inch (minimum) hose. (Furnished by Exxon).
37. Trip tank. (Furnished by Exxon).
38. 6-inch 3,000 psi minimum WP manual or pressure operated gate valve.

NOTES:

1. Items 9 and 10 may be replaced with double ram type preventer. Any side outlets shall be double valved or blind flanged.
2. Only type U, LWS and QRC ram type preventers with secondary seals are acceptable.
3. The two valves next to the stack on the kill and fill line to be closed unless string is being pulled.
4. Kill line is for emergency use only. This connection shall not be used for filling.
5. Replacement rams for each size drill pipe in use and blind rams shall be on location at all times.