		ı	-			
NO OF COPIES RECEIVED				Form C-103		
DISTRIBUTION		1				Supersedes Old
NTA FE			NEW MEXICO OIL CONSE	RVATION COMMISSION		C-102 and C-103 Effective 1-1-65
	1 : 1	<u>,</u>		RECE	IVE	D
J.S.G.S.						5a. Indicate Type of Lease
AND OFFICE				007 0 0	1075	State X Fee
JPERATOR	1			<b>o</b> ct 2 3	1975	5. State Oil & Gas Lease No.
				·····		L-4679
(DO NOT USE THIS F	SUI	NDRY	Y NOTICES AND REPORTS ON A POSALS TO DRILL OR TO DEEPEN OR PLUG BA	WELLS D. C.	OFFICE	
						7. Unit Agreement Name
OIL GAS			OTHER- Dri	lling		
. Name of Operator				<b></b>		8. Farm or Lease Name
Coquina Oil Corporation						HNG State
Address of Operator						9. Well No.
P. O. Drawer 2960, Midland, TX 79701						1
t. Location of Well						10. Field and Pool, or Wildoat
UNIT LETTERG	······ •	19	180 FEET FROM THE North	LINE AND1980	FEET FROM	Wildcat
						AIIIIIIIIIIIIIIIIIIIA
THE Last	LINE, S	EC TION	N36 TOWNSHIP23-S	RANGE 27-E	NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)						12. County
						Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
NOT			TENTION TO:	3083	EQUENT	REFORT OF.
PERFORM REMEDIAL WORK			PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON				COMMENCE DRILLING OPNS.		PLUG AND ABANDONMENT
PULL OR ALTER CASING			CHANGE PLANS	CASING TEST AND CEMENT JO		plation [V]
				OTHER Drilling	10 001	pletion X
OTHER						

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903.

Spudded Oct 8, 1975, @ 1:30 PM. October 9, drld 17 1/2" hole to 501', ran 13 jts of 13 3/8" 68# K-55 STC 8rd casing, landed @ 500.09'. Cemented w/325 sxs Howco Lite Wate & 150 sxs Class C w/1/4# Flocele, 2% CaCl<sub>2</sub> in all cement. Circ 40 sxs to pit. Plug displacement w/70 bbls FW. Plug down @ 9:20 AM, 10-9-75. WOC 18 hrs. Tested to 500 psi - held OK. October 17, drilled 12 1/4" hole to 2956'. Ran 73 jts 9 5/8" 36# K-55 LTC 8rd casing, landed @ 2953.82'. Cemented w/800 sxs Howco Lite Wate, 5# Gilsonite/sx + 200 sxs Class C, 2% CaCl<sub>2</sub> & 1/4# Flocele in all cement. D'splaced w/228 BFW. Plug down @ 7:55 PM, Oct 15. WOC 18 hrs. Tested 1500 psi - Held OK. October 19, drlg ahead w/8 1/2" hole @ 4067' - No problems.

CONDITIONS OF APPROVAL, IF ANY: