


NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

NEW MEXICO OIL CONSERVATION COMMISSION



Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State ☐	Fee ☒
5. State Oil & Gas Lease No.	16150A&B	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER- _____

2. Name of Operator
Belco Development Corporation ✓

3. Address of Operator
10000 Old Katy Road, Suite 100, Houston, Texas 77055

4. Location of Well
UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM
West LINE, SECTION 5 TOWNSHIP 22-S RANGE 27-E NMPM.

7. Unit Agreement Name	
8. Farm or Lease Name	Jarvis Mead <i>CHL</i>
9. Well No.	1
10. Field and Pool, or Wildcat	C. Carlsbad <i>MOR (Atoka)</i>
12. County	Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3141' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☒	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☐
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set BP @ 11,100' & dump ^{35'} 20' cement on top blanking off existing Morrow perf. 11,218'-24', 11,128'-38' & 11,114'-22'.
- TIH w/RBP & RTTS. Set RBP @ approx. 11,070' & RTTS tool at approx. 10,800'. Perf 11,036'-53', w/2 SPF, test & acidize if necessary.
- Release RTTS tool & retrieve BP. Set RBP at approx. 10,830' & RTTS tool at approx. 10,500'. Perf. 10,778-98' & 10,664'-74' w/ 1SPF. Break down perfs. & test.
- Release RTTS tool & retrieve BP. Set BP at approx. 10,460' & RTTS tool @ approx. 10,175'. Perf. 10,422'-37' w/2 SPF. Test and determine productivity.
- If zone not commercial, TOH w/RTTS tool & BP.
- TIH w/pkr & set at approx. 10,350'.
- Acidize perf. 11,053'-10,422' w/6000 gal. acid containing 1000 SCF N₂/bbl. Test & determine productivity.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>Carl M. Hansen</i>	TITLE Production Superintendent	DATE 12-7-83
APPROVED BY _____	Original Signed By Leslie A. Clements Supervisor District II	DATE DEC 12 1983

CONDITIONS OF APPROVAL, IF ANY: