

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions
reverse side)

TE
TE

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 19841

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry

2. NAME OF OPERATOR

I. W. Lovelady

3. ADDRESS OF OPERATOR

P. O. Drawer 2666; Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 660' FEL of Sec. 24

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indian Draw (Delaware)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-22-S, R-27-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3073.8 Gr.

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Drilling

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 6-3/4" hole to 3380': Ran open hole logs. completed 4:00 P.M. 1/17/76.

2. Found no sand development in Old Indian Draw (Delaware) pay.

We respectfully request permission to plug & abandon this well as follows:

1. Spot cement plugs W/Halliburton pump & class "H" cement:

a. 25 Sks. - 3225 - 3125'
b. 25 Sks. - 2300 - 2200'
c. 35 Sks. - 520 - 420'
d. 15 Sks. - 20 - Surface

2. Install permanent regulation marker.

3. Clean location, cover pits, & restore area to original level.

NOTE: Plugging Procedure Discussed W/District Office In Artesia.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Hamm, Jr.

TITLE Production Supt.

DATE 1/23/76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED

JAN 26 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO