

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

RECEIVED

Southeastern New Mexico

Northwestern New Mexico

OCT 13 1976

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn 10,060'	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka 10,216'	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss 11,654'	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand 1,980'	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs 5,390'	T. Wingate _____	T. _____
T. Wolfcamp 8,440'	T. Lamar 1,914'	T. Chinle _____	T. _____
T. Penn. _____	T. Cherry Canyon 2,922'	Permian _____	T. _____
T. Cisco (Bough C) _____	T. 3rd Bone Spring 8,118'	Penn. "A" _____	T. _____
	T. Morrow 11,002'		

O. C. C.
ARTESIA, OFFICE

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1860	1860	Surface sands, anhydrite and salt				
1860	4285	2425	Lime, sand & Dolomite				
4285	8118	3833	Lime, shale & sand				
8118	10060	1942	Lime & shale				
10060	10216	156	Lime & shale - Strawn				
10216	11002	786	Lime, sand & shale - Atoka				
11002	11654	652	Lime, sand & shale - Morrow				
11654	11681	27	Lime & shale - Mississippian				