

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
 MAY 5 1976
O. C. C.
 ARTESIA, OFFICE

Form O-103
 Superseded Old
 O-102 and O-105
 Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
6. Unit Agreement Name
7. Operator Name CNB Com.
8. Well No. 1
9. Field and Pool Name Undes. Mataga Morrow Gas
10. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-
2. Name of Operator BURMAH OIL AND GAS COMPANY
3. Address of Operator 600 Western United Life Building, Midland, Texas 79701
4. Location of Well UNIT LETTER <u>L</u> <u>1780</u> FEET FROM THE <u>south</u> LINE AND <u>660</u> FEET FROM THE <u>west</u> LINE, SECTION <u>11</u> TOWNSHIP <u>24-S</u> RANGE <u>28-E</u> NMPH.
11. Elevation (Show whether DF, RT, GR, etc.) 2996' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING Casing <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting on proposed work) SEE RULE 1103.

Spudded well at 2:00 pm 4-24-76.

Drilled 17-1/2" hole to 631'. Ran 630' 13-3/8" 54.5#, K-55 casing. Cemented w/485 sacks class "C" cement. Circulated 75 sacks cement. WOC 24 hours.

Installed BOP and tested casing to 1000 psi before drilling shoe. Pressure held at 1000 psi.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Stauffer R. E. Stauffer

TITLE Sr. Drilling Engineer

DATE 5-4-76

APPROVED BY W. A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE MAY 10 1976

CONDITIONS OF APPROVAL, IF ANY: