Form 3160-5 (June 1990)

1. Type of Well

12.

2. Name of Operator

Final Abandonment Notice

Subsequent Report

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

					asr
rm 3160-5 ine 1990) Do not use this	DEPARTMENT	ED STATES OF THE INTERIOR AND MANAGEMENT AND REPORTS ON WE I or to deepen or reentry PERMIT—" for such pro	Dnawer Diagram D. Artesia, LLS 1/25 1/4 103	NM - 17589 6. If Indian, Allouse or Tribe Na	No.
		IN TRIPLICATE	00T - 6 1993	7. If Unit or CA, Agreement De	Signation
. Type of Well Gas Other Other Other				Nash Unit 8. Well Name and No. Nash Unit #5	
2. Name of Operator	roduction Compan	9. API Well No. 30-015-21800			
3. Address and Telepho P.O. Box	1030, Roswell,	10. Field and Pool, or Explorator Undesignated B			
4. Location of Well (Fo	2310' FSL & 33 Section 13-23S	11. County or Parish, State Eddy, New Mexi	ico		
12. CHEC	CK APPROPRIATE BOX	s) TO INDICATE NATU	RE OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent		Abandonme Recompleti		Change of Plans New Construction Non-Routine Fracturing	
		n	- ale	── MOS-KORITHE LESCITIONS	

Water Shut-Off

Dispose Water

Conversion to Injection

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging Back

Casing Repair

Altering Casing

cement

Other Re-entry, casing,

Spud drilling cement plugs at 8:00 07/21/93: MIRU Grace Drilling Rig #348. PM on 7/21/93. Weld head. NU BOP. Test to 1500#. Held OK.

Ran 177 joints (7307.61') 5 1/2" 17# J55 07/31/93: Drilled to 7300' TD. casing. Cemented at 7300' First Stage with 335 sacks 50/50 Poz H with 5 # D-44, 3 % D-60, 2.5 # B-28 and 1/4 # D-29 per sack. Circulated 77 sacks cement to pit. Plug down at 6:45 AM on 8/1/93. Cemented Second Stage with 460 sacks 50/50 Poz H with 5# D-44, 3% D-60, 2.5# B-28 and 1/4# D-29 per sack. Second Stage could not bump plug. Plug down at 12:15 PM on 8/1/93.

08/01/93: Ran Temperature Survey. Top of cement at 3700'.

CONTINUED ON ATTACHMENT

4. I hereby certify that the foregoing is to Signed And J.	nue and correct Title Production Rec	cords Manager Date 9/2/93
(This space for Federal or State office	use)	ACCEPTED FOR RECORD
Approved by	Tide	4. Lora 6CT - 4 1993
Title 19 11 S.C. Section 1001 makes it a	crime for any person knowingly and willfully to make to any department	or agency of the United States any false, fictisious or fraudulent statements
or representations as to any matter within	its jurisdiction. *See Instruction on Reverse Sid	CARLSBAD, NEW MEXICO