

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Injection

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 330' FNL X 668' FEL, Sec. 19
AT TOP PROD. INTERVAL: (Unit A, NE/4, NE/4)
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 1-7-81. Pulled rods and tubing. Perforated 3286'-95' and 3303'-28' with 4 JSPF. Ran packer and tubing and set packer at 3250'. Acidized well with 1000 gallons 7-1/2% clay stabilizing acid tagged with 1 MC radioactive material. Flushed with 15 bbls. of fresh water. Pulled tubing and packer and ran injection packer and plastic coated tubing. Set packer at 3203'. Placed well on injection.

0+4-USGS, A

1-Hou

1-Susp

1-GPM

Subsurface Safety Valve: Manu. and Type

Set @ 42 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Greg Mitchell

TITLE A. S. Adm. Analyst DATE 3-4-81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAR 9 1981

U.S. GEOLOGICAL SURVEY
POWELL, NEW ME