Form approved.

(May	1963) O LO S'AA F DEDADEM F OF THE		Budget Bureau No. 42-R1424.
			5. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL SU	JRVEY	NM-14761 & LC 064200
	SUNDRY NOTICES AND RE	PORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	(Do not use this form for proposals to drill or to deep	Den or plug Eckin a-different reservoir	1
	(Do not use this form for proposals to drill or to deep Use "APPLICATION FOR PERMIT-	" for such proposals.	1
1.			7. UNIT AGREEMENT NAME
011 W1	ELL GAS OTHER	Alicon	
2. NA	AME OF OPERATOR	AUG 2 7 1978	8. FARM OR LEASE NAME
	C & K Petroleum, Inc.		Dannari Fadanal Hitth
3. AD	DRESS OF OPERATOR	9. c. r:	Pennzoil Federal "15"
	600 C & K Petroleum Bldg. M	idland, Tx. 79701 FFICE	
4. LC	CATION OF WELL (Report location clearly and in accordan	ace with any State requirements.*	10. FIELD AND POOL, OR WILDCAT
Se	ee also space 17 below.) t surface		fered,
10	80' FC & 1080' FU lines Co. 15	m 9/ C p 9/ m m 11 c	White City (Penn) 11. SEC, T., R., M., OR BLK. AND
	80' FS & 1980' FW lines, Sec. 15,	1-24-5, R-26-E, Eddy Co.	SURVEY OR ARMA
иe	w Mexico.		
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			Sec. 15, T-24-S, R-26-E 12. COUNTY OR PARISH 13, STATE
11, 11	ISSUE NO.	whether br, ki, Gk, etc.)	12. COUNTY OR PARISH 13. STATE
			Eddy New Mexico
16.	Check Appropriate Box To	Indicate Nature of Notice, Report	or Other Data
	NOTICE OF INTENTION TO:		
	NOTICE OF INTENTION TO:	s s	UBSEQUENT REPORT OF:
Т	EST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
£	FRACTURE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
5	SHOOT OR ACIDIZE ABANDON*	SHOOTING OR ACIDIZIN	IG ABANDONMENT*
F	REPAIR WELL CHANGE PLANS	(Other) Spuddir	ng & Running Casing
((Other)	(NOTE: Report	results of multiple completion on Well ecompletion Report and Log form.)
17. DE	SCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all pertinent details and size portinent	dates including estimated date of starting and
	proposed work. If well is directionally drilled, give sul nent to this work.) *	osurface locations and measured and true	vertical depths for all markers and zones perti-
Α.	Spudded: 9:45 PM, 6-15-76		-
	·		
В.	Drilled 17-1/2" hole to 497', se	et 13-3/8", 48# casing, @	497'. Cemented with
	450 sx. class "C" cement , circu	lated to surface. Plug	down @ 5:45 PM 6-16-76
	WOC 15 hrs. Tested with 500# 30	min held O-K.	20 70.
		,	ν
C.	Drilled 12-1/4" hole to 5450'.	Set 8-5/8", 32# & 24# ca	sino d 5450! Comentad
	with 3137 sx., circulated to sur	face. Plug down @ 1.22	PM 7-1-76 LIOC 22 hrs
	Pressure tested with 1000# 30 mi	n held O-K	111, 7-1-70. WOG 22 HIS.
	110000 10000 1110 1000 1 30 mg	integration in the second seco	
D.	Drilled 7-7/8" hole to 11 760!	Cot 5 1/211 17/4 c 20/4	
υ.	Drilled 7-7/8" hole to 11,760'.	Set 3-1/2", 1/# & 20# c	asing @ 11,/60'. Cemented
	with 1100 sx. Plug down @ 7:50 cement @ 6910'.	rm, 8-0-/0. Kan temp. s	urvey; found top of
	cement & bylo.		
			RECEIVED
			MEGETVED
			AUG26 1970
			·
			U. S. GEOLOGICAL GURVEY
			ARTESIA, NEW MEXICO
			grant of the second second second
18. I	hereby certify that the foregoing is true and correct		
	(19) 10 (11)	A Amazada para e e	
SI	GNED 121 C.	ritle Administrative Supe	rvisor DATE August 24, 1976

6 (This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE . *See Instructions on Reverse Side

DOLLEL MAN LENGON