

Husky Oil Company
Forehand-Delaware #2
1880' FLS & 1980' FWL
Sec. 15 T23S R27E
Eddy County, New Mexico

DRILL STEM TEST

DST #5 - 3297 - 3366'

Tool open: 5:30 a.m. 7/21/76.

5 min. pre-flow: Immed. strong blow air. G.T.S. 5 mins.
after SI, bypass to 2" - 6" orange flame. ISI - 60: 5:35 a.m.;
open 6:35 a.m.

Open for flow: Immed. good blow gas - 6' flame.

1/8" Ch - 40#	in	5 mins.	=	18.2 MCF.
52#	" 20 "		=	22.2 "
58#	" 30 "		=	24.2 "
59#	" 40 "		=	24.3 "
58#	" 60 "		=	24.2 "

FSIP; - 7:35 - 9:35 a.m.

Out of hold w/test tool @ 10:00 a.m. 7/21/76.

Rec: 2875' G.I.D.P. 390' blk salty S₂ wtr.

Res. - .12 @ 78°F; 57,000 ppm Cl.

(Pit sple - .7 @ 70°F; 10,000 ppm

Sple. Chamber Rec. - 500 cc blk salty S₂ wtr

0 Cu ft Gas - 210# pres.

Res. .12 @ 78°F; 57,000 ppm

IHP - 1608

IFP - 119 - 32

ISI (60) - 1586

FFP - 119 - 236

FSI (120) - 1586

FHP - 1608