

Husky Oil Company
Forehand-Delaware #2
1880' FSL, 1980' FWL
Sec. 15 T23S-R27E
Cass Field
Eddy County, New Mexico

CORE DESCRIPTIONS

Core #1 - 2097.5 - 2129'

Recovered 31½'-100% Interbdd Dolo, sh & ls. hd & dnse w/no shows.
Delaware ls interval. Start coring: 9:40 a.m. 7/13/76.

Coring Time:

2097.5-2100	6	13	13	(w/10,000#)						
	12,000 @ 2101; 14,000 @ 2102; 16,000 @ 2105									
2100-2110	9	8	8	9	8	7	7	7	7	7
2110-2120	8	8	8	8	7	7	6	7	8	8
	Conn. @ 2125									
2120-2129	7	9	9	8	8	9	11½	11	11	

Finish coring: 2:10 p.m. 7/13/76, 100% Recovery.

Brief Core Descriptions

2097½-2001	Sh - dk, gry, brn, dolo, n.s. tite.
2001-2004	Dolo - li gry, fnly x-ln, tite, n.s.
2004-2005	Sh - dk gry.
2005-2011	Dolo - li gry, tan fnly x-ln, tite, n.s.
2011-2012	Sh - med to dk, gry, mica.
2012-2019	Dolo - med gry, tite n.s.
2019-2022	Sh - gry, 100 units gas.
2022-2027	Ls - tan, buff, fnly-x-ln, tite, n.s.
2027-2028	Sh - brn to gry
2028-2029	Ls - buff, tan, fnly x-ln, sh partings. (Cond: Gas from shale)

Core #2 - 2305.8 - 2345-39.2'

Recovered 100%

Drilling Time:

2305.8-2310	3	6½	4½	4	2					
2310-2320	3	2	2½	2	2	2	1½	2	2	3
2320-2330	3	3	3	3	3	4	4	3	3	3
2330-2340	3	4	3	3	3	3	3	3	3	3
2340-2345	4	3	3	3	3					

Brief Core Descriptions

2305-2320	Ss - li gry, vfg, friable, subrdd, clear, transparent, scattered li tan, grn & red qtz grains, v/dull gold fluor, slow leaching on cut. bright li blue, along edges of chip @ 2314-26. Scattered patches of stained appearance. Faint gussy odor on fresh break. @2307.5'-3" shale parting dk gry, hd, dolomitic.
-----------	---