

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved  
Budget Bureau No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 0554481

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

**RECEIVED**

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

SEP 21 1976

2. NAME OF OPERATOR

The Eastland Oil Company

3. ADDRESS OF OPERATOR

704 Western United Life Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980 feet NSL and 660 feet FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3102' GR, 3112' DE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Union Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Esperanza Delaware

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 11, T22S, R27E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing Setting

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 11" hole at 8:30 a.m. 9-12-76 and drilled to 424 feet. Ran 13 joints 24#, J-55, 8R, ST&C 8-5/8" #2 casing, 409' set @ 421'. Cemented w/200 sacks Class C w/2% CaCl<sub>2</sub>. Cement in place at 1:30 p.m. 9-12-76. Top of cement 34 feet from surface. Recemented outside of 8-5/8" casing with 2 yards of ready mix to surface. Allowed cement to set 12 hours. Nippled up and tested casing with 1000 psi for 30 minutes. with no pressure leak-off. Drilled cement plug at 7:30 a.m. 9-13-76.

**RECEIVED**

SEP 17 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Superintendent

DATE 9-16-76

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE SEP 17 1976

CONDITIONS OF APPROVAL, IF ANY: