

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
NOV 29 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTEBIA, OFFICE

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator FEATHERSTONE DEVELOPMENT CORPORATION ✓	8. Farm or Lease Name McCoy
3. Address of Operator 1717 West Second Street, Roswell, NM 88201	9. Well No. 1
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 835 FEET FROM THE East LINE, SECTION 22 TOWNSHIP 23S RANGE 26E NMPM.	10. Field and Pool, or Wildcat UND. CARLSBAD MORROW GAS
15. Elevation (Show whether DF, RT, GR, etc.) 3298' GR.	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-28-76 Spud 17" hole.
9-30-76 Ran 608' 13 3/8" surface casing. Circulated cement.
10-15-76 Ran 5250' 8 5/8" casing and cemented 1100 sacks. Calculated top cement @ 1780'
11-24-76 TD - 11,954' - Ran logs preparing to plug and abandon.
Propose to plug and abandon as follows:

100' cement plug 35 sacks 11,460' - 11,360' Morrow
100' cement plug 35 sacks 10,032' - 9,932' Canyon
100' cement plug 35 sacks 6,500' - 6,400' Bone Springs
100' cement plug 35 sacks 5,300' - 5,200' Bottom 8 5/8" casing.
Shot 8 5/8" @ 1,494' and pulled.
100' cement plug 57 sacks 1,544' - 1,444' 8 5/8" stub.
15 sacks at surface and set 4 1/2" marker pipe 4' above surface.
Pits will be filled and location leveled prior to abandonment.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

FEATHERSTONE DEVELOPMENT CORPORATION
SIGNED Charles W. Hicks TITLE Vice President DATE 11-26-76
(Charles W. Hicks)

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE NOV 30 1976

CONDITIONS OF APPROVAL, IF ANY: spud 100' plug 10200-300 + 8830-8930
100' 11 550-650