

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NR RECEIVED	
2. NAME OF OPERATOR Gulf Oil Corporation ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME MAR 12 1982	
3. ADDRESS OF OPERATOR P. O. Box 670, Hobbs, NM 88240		7. UNIT AGREEMENT NAME O. C. D.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FNL & 1980' FEL		8. FARM OR LEASE NAME, OFFICE Franklin et al Federal	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3973' GL		10. FIELD AND/TOOL, OR WILDCAT Strawn	
		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec 9-T24S-R24E	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

POH with production equipment. Set CIBP at 8400', circulate mud laden fluid. Spot 10 sack cement plug on CIBP. Cut 5½" casing at 6805', POH with casing. Spot 60 sack cement plug 6875'. Tag plug at 6609'; spot 45 sack cement plug 5000'. Spot 45 sack cement plug at 2650'. Tag plug at 6679'; spot 150' cement plug 5500'. Spot 150' cement plug 4050'. Spot 100' cement plug 2650'-2550'. Spot 55 sacks cement 2646'. Tag cement at 2520'. Spot 25 sack surface plug. Set dry hole marker, clear and clean location. P&A complete 3-25-81.

APPROVED

(Orig. Sgd.) PETER W. CHESTER

MAR 11 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISORPosted ID-2
P+A
3-19-82

18. I hereby certify that the foregoing is true and correct

SIGNED

R. D. Pith

TITLE

Area Engineer

DATE

3-30-81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCCL

RECEIVED

APR - 9 1981

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO