(Mag 1963) DEPAR	L TED STAT	es Interi		Bud Bud	m approyed. get Bureau N IGNATION AND		
(Do not use this form for pro Use "APPI	DTICES AND REP oposals to drill of to deep lication for permit-			6. IF INDIAN,	ALLOTTEE OR	TRISE NAME	
1. OIL GAS X OTHER WELL WELL OTHER 2. NAME OF OPERATOR	3	NDV	<u>04 474</u>	7. UNIT AGRE White Com Uni 8. FARM OR I		n Gas	
Gulf Oil Corporati	Lon						
P. O. Box 670, Hobbs, NM 88240				9. WELL NO.	9. WELL NO.		
 Co. Box Crob, HODDS, ALL CO240 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 					10. FIELD AND POOL, OR WILDCAT		
At surface					White City Penn		
2310' from north line and 2310' from west line Section 28, T-24-S, R-26-E				11. SEC., T., F SURVEY	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
Deceion 20, 1-2	14-5, K-20-L			28 24	4-S 26-E		
14. FERMIT NO.	15. ELEVATIONS (Show 3393		RT, GR, etc.)	12. COUNTY O Eddy	DR PARISH 13	. state New Mex	
Check	Appropriate Box To I	Indicate N	lature of Notice, Report,	or Other Data			
NOTICE OF IN	TENTION TO:		SU	BSEQUENT REPORT OF	•		
TEST WATER SHUT-OFF	FULL OR ALTER CASING		WATER SHUT-OFF	X RE	PAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT		TERING CASING	;	
SHOOT OR ACIDIZE	ABANDON* Change plans		SHOOTING OR ACIDIZING (Other)	AB	ANDONMENT*	· · · · · · · ·	
(Other)			(NOTE: Report re	esults of multiple concompletion Report ar		Vell	
total depth of 13-3 of 10-3/4" OD 40.50	3/4" hole 1900')# K-55 ST&C Cas	at 3:45 sing. S	et and cemented at	45 jts and 1 1900' with	l cut jt 300 sx i	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce with 2000# 30 minut	8/4" hole 1900' D# K-55 ST&C Cas ement and 300 sx ces - OK.	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1 1900' with	l cut jt 300 sx i	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce	8/4" hole 1900' D# K-55 ST&C Cas ement and 300 sx ces - OK.	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1 1900' with	l cut jt 300 sx i	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce with 2000# 30 minut	8/4" hole 1900' D# K-55 ST&C Cas ement and 300 sx ces - OK.	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1 1900' with	l cut jt 300 sx f casing	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce with 2000# 30 minut	8/4" hole 1900' D# K-55 ST&C Cas ement and 300 sx ces - OK.	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1 1900' with Cl ₂ . Tested	l cut jt 300 sx f casing	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce with 2000# 30 minut	8/4" hole 1900' D# K-55 ST&C Cas ement and 300 sx ces - OK.	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1 1900' with 12. Tested	l cut jt 300 sx f casing IVED 1976 Al SURVEY	1880'	
total depth of 13-3 of 10-3/4" OD 40.50 mix, 600 sx lite ce with 2000# 30 minut	3/4" hole 1900' # K-55 ST&C Cas ement and 300 sx es - OK. -1/2" hole at 19 -1/2" hole at 19	at 3:45 sing. S class	PM 11-15-76. Ran et and cemented at C Neat with 2% Ca(45 jts and 1900' with Cl ₂ . Tested NOV 22 U.S. GEOLOGIC ARTESIA, NEV	l cut jt 300 sx f casing IVED 1976 Al SURVEY	1880' thick	