

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI
(Other instructio.
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-065347

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

White City Penn Gas Com Unit No. 3

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' FN & WL, Section 28, 24-S, 26-E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

White City Penn Gas Com Unit No. 3

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

White City Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28, 24-S, 26-E

14. PERMIT NO.

15. ELEVATIONS (Show whether ~~at~~ RT, CR, etc.)

3393' GL

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SURSEQUENT REPORT OF:

WATER SHUT-OFF

XX

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11,512' Total Depth.

Reached total depth of 6-1/2" hole at 11,512' at 1:15 AM, December 21, 1976. Ran 83 joints, 3432' of 5" OD 17.93# N-80 Atlas Bradford FL47 liner. Set bottom of liner at 11,511' and top at 8072'. Cemented with 465 sacks of Class H cement with 5# KCL per sack, .8% Halad 22, .4% CFR2. WOC 24 hours. TOC at 8072'. Cleaned out and liner would not hold pressure. Squeezed top of liner with 200 sacks of Class H cement. WOC over 24 hours. Cleaned out and tested liner with 3100#, 30 minutes, OK.

RECEIVED

JAN 03 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

D.F. Berlin

TITLE

Area Engineer

DATE December 29, 1976

(This space for Federal or State office use)

APPROVED BY

Joe L. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 4 1977

CONDITIONS OF APPROVAL, IF ANY: