

NM OIL CONS. COMMISSION
Drawer 10
Albuquerque, NM 88210

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1001 N 2289E 330' FSL X 330' FSL, Sec. 18

AT TOP PROD. INTERVAL: T-22-S, R-28-E, Unit 1

AT TOTAL DEPTH: 6

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED
OCT 2 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 6-24-80. Pulled 2-3/8" tubing with seating nipple and ran correlation log from 3374' to 2500' and ran a retrievable bridge plug set at 3290'. Perforated Delaware intervals 2894'-2900', 2995'-3001', 3055'-64', 3180'-82', 88'-90', 95'-97', 3255'-60', and 64'-70', w/2 DPJSPF. Ran 2-3/8" tubing and packer set at 2800' with tailpipe and retrievable tool set at 2835'. Swabbed. Acidized down 2-3/8" tubing and 2000 gals. 7-1/2% NE acid and flushed w/20 bbl. brine water. Bled down and ran swab. Started flow at surface and swabbed 28 hrs. Recovered 264 BLW and 302 BW. Released packer and ran 2-3/8" tubing and packer and bridge plug retrievable tool at 3290'. Released retrievable bridge plug and pulled tubing, packer, and bridge plug. Ran seating nipple with 2-3/8" tubing set at 3333'. Moved out service unit 7-1-80. Pumped 1134 BW and 15 BNW in 134 hrs. Pulled rods, pump, and tubing. Ran tubing and shut-in with no further work to be done until additional workover evaluated.

0+4-USGS, H 1-Hou 1-Susp 1-CLF
Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy L. Gorman TITLE Ast. Adm. Analyst DATE 9-29-81

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD

PETER W. CHESTER

OCT 14 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE

DATE

APPROVED FOR 6 MONTH PERIOD
ENDING MAR 14 1982

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.