

DISTRIBUTION	
SANITARY	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JAN 15 1979

O.C.C.

SUNDRY NOTICES AND REPORTS OF WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" - FORM C-1011 FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER ☒ Temporarily Abandoned Well

2. Name of Operator
Belco Petroleum Corporation ✓

3. Address of Operator
10,000 Old Katy Rd. Suite 100, Houston, Texas 77055

4. Location of Well
UNIT LETTER C 1650 FEET FROM THE West LINE AND 990 FEET FROM
THE North LINE, SECTION 20 TOWNSHIP 22-S RANGE 27-E NEARBY.

15. Elevation (Show whether DF, RT, GR, etc.)
3128.2 GR

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Form or Lease Name
Martin Com.

9. Well No.
4

10. Field and Pool, or Wildcat
S. Carlsbad-Cherry Canyon

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☒	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/1/77 This well was temporarily abandoned. Casing was run but well was never perforated.

Plugging Procedure:

1. Cut 5½" casing @ freepoint & spot a 100 sx. cmt. plug.
2. Pull casing to 525' & spot a 100 sx. cmt. plug from 325' to 525'.
3. Pull & LD 5½" casing.
4. Spot a 10 sack cmt. plug @ surface.
5. Erect monument & clean up location.

Well Facts:

1. TD 3400'
2. 8-5/8" surface casing set @ 426' w/240 sx. cmt. Cement circulated.
3. 5½" Production casing set @ 3400' w/750 sx. cmt. Casing was never perforated.

TOC 1350

Anticipated plugging date, March 1, 1979.

* 5½" casing stub plug and 8½" shoe plug must be pumped thru 2" tubing + tagged

* Intervals between plugs filled w/ mud.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. C. Ball / J.C. Ball TITLE Production Engineer DATE 1/11/79

APPROVED BY W. A. Gressett SUPERVISOR, DISTRICT II DATE JAN 16 1979

CONDITIONS OF APPROVAL, IF ANY:
* as noted above.

Notify N.M.O.C.C. in sufficient time to witness
Plugging