

copy to SF

Form 9-511
(May 1965)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. **RECEIVED**

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670 Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1650' FSL & 1650' FEL, Section 19, T-24-S, R-26-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3436' GL

5. LEASE DESIGNATION AND SERIAL NO.

LC-065347

6. IF INDIAN, ALIQUOTED OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Estill "AD" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

White City Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T-24-S, R-26-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 6 1/2" hole to 11,600', complete 6-7-77. Ran 87 Jts of 5" 18# N-80 X-Line liner. Set and cemented at 11,600'. Top of liner at 8112'. Cemented with 400 sacks class H with .6% Halad-22, .3% CFR-2 and 5# KCL per sack. Cement circulated to top of liner. WOC 22 3/4 hours. Cleaned out to 11,556'. Tested liner with 2500# for 30 minutes - OK.

RECEIVED

JUN 15 1977

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

O. F. Berlin

TITLE

Area Engineer

DATE

June 14, 1977

(This space for Federal or State office use)

APPROVED BY

Lee D. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 16 1977

CONDITIONS OF APPROVAL, IF ANY: