

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM
68-06808

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

PERRY R. Bass ✓

SEP 22 1980

3. ADDRESS OF OPERATOR

Box 2760 MIDLAND TX 79702

O. C. D.

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations.
See also space 17 below.)
At surface

1450' FNL & 1830' FEL OF SECTION - UNIT LETTER G.

7. UNIT AGREEMENT NAME

JAMES RANCH UNIT

8. FARM OR LEASE NAME

JAMES RANCH UNIT

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 21, T22S, R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH 13. STATE

EDDY N. MEX.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SPUD DATE & SURF. CSG

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

SPUDED 17 1/2" HOLE @ 9:00 PM, SEPTEMBER 4, 1980.

DRILLED 17 1/2" HOLE TO 540'. RAN 13 TTS + CUT OFF JOINT -
13 3/8" 48" H-40 STVC CASING + FLOAT COLLAR & GUIDE SHOE.
SET @ 534.42'. CEMENTED W/500 SKS CLASS "C" + 2% COCL₂. DID
NOT CIRCULATE. RAN 5 TTS 1" - CEMENTED W/500 SKS CLASS "C".
CIRC OUT 40 SKS. WOC 24 HOURS. TESTED BOPE & RAMS TO
1000# - TESTED HYDRAULIC TO 1000# - DRILLED FLOAT & SHOE - TESTED
TO 800# - ALL HELD OK. COMMENCED DRILLING 1 1/2"

ACCEPTED FOR RECORD

SEP 18 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

RECEIVED

SEP 17 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H. O. Dwyer Jr.

TITLE

Sr. Production Clerk

DATE

Sept. 16, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.