

Form 9-331
(May 1963)C/SF
J. L. W.UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 06808

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

PERRY R. BASS

3. ADDRESS OF OPERATOR

Box 2760, MIDLAND, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1450 FNL + 1830' FEL OF SECTION - UNIT LETTER G.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3161.8' GL 3180.3' ICB

7. UNIT AGREEMENT NAME

James Ranch Unit

8. FARM OR LEASE NAME

JAMES RANCH UNIT

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

WILDCAT McCLINTOCK

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 21, T22S, R. 30E

12. COUNTY OR PARISH

EDDY

13. STATE

N. MEX.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) 9 5/8" CSG, DST #1 + 5 1/2" CSG X
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRLD 12 1/4" HOLE TO 3729'. RAN 89 JTS 9 5/8" 36# STVC CSG
W/FLOAT & SHOE. SET @ 3726.59' W/1725 SKS LITE & 250 SKS CLASS C.
PLUG DOWN @ 8:00 AM 9-13-80. CIRC OUT 300 SKS. FLOATS HELD. WOC 24
HOURS. TESTED BOPE & CASING SEAT - HELD OK. COMMENCED DRLG
8 3/4" HOLE. RAN DST #1 - 6972' - 7030' (DELAWARE) - SEE ATTACHED.
DRLD 8 3/4" HOLE TO 14,200'. RAN 346 JTS 5 1/2" 17# CSG. CEM W/435
SKS LITE & 895 SKS CLASS H. PLUG DOWN @ 4:30 PM 12-6-80. FLOATS
HELD. TOC BY TEMP SURVEY @ 9590'. PBTD 14,110'. RELEASED RIG
@ 10:00 AM CST 12-7-80. 5 1/2" CSG SET @ 14,155.33'.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. W. Murty, Jr.

TITLE

Sr. Prod. Clerk

DATE

Jan. 20, 1981

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD

PETER W. CHESTER

TITLE

DATE

JAN 22 1981

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side
NEW MEXICO