

1. COPIES RECEIVED	3
DISTRIBUTION	
SALES	1
FILE	1
PLANS	
FIELD OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 3 1977

Form O-101
Superseded 10/1
C-101 and C-103
Effective 1-1-75

5. Title of Project	6. Date	7. Page
		1

SUNDY NOTICES AND REPORTS OF O. C. C. ARTESIA OFFICE

DO NOT USE THIS FORM FOR OPERATIONS TO BE CARRIED OUT IN THE ARTESIA OFFICE RESERVOIR.

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator **HNG OIL COMPANY**

3. Address of Operator **P. O. Box 2267, Midland, Texas 79702**

4. Location of Well

UNIT LETTER **F** **2310** FEET FROM THE **North** LINE AND **2310** FEET FROM **West** LINE, ELEVATION **29** TOWNSHIP **23S** RANGE **28E** RANGE

15. Elevation (Show whether DF, RT, GR, etc.) **GR - 3095.8**

8. Type of Operation

9. Well No. **Pardue Farms 29**

10. Field No. **1**

12. County **Eddy**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
☐ PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER	☐ PLUG AND ABANDON ☐ CHANGE PLANS ☐ REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☒ CASING TEST AND CEMENT JOBS ☐ OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

CASING DETAIL

7-1-77	22.00'	1 jt. 8-5/8"; 24#; K-55; ST&C; Class "A"; (Out 16.18 - Cut joint in 5.82)
	665.90'	17 jts. 8-5/8"; 24#; K-55; ST&C; Class "A"
	1.50'	Halliburton Float Collar
	78.15'	2 jts. 8-5/8"; 24#; K-55; ST&C; Class "A"
	1.08'	Halliburton Float Shoe
	768.63'	TOTAL; Set @ 764'

W.O.C. 18 1/2 hrs.

Cmt. w/300 sx. Trinity Light Weight w/2% CaCl₂ & 1/4# Celloflake; Mixed @ 12.2 ppg; followed by 150 sx Class "C" w/2% CaCl₂ & 1/4# Celloflake; Mixed @ 14.6 ppg; Circ. 20 sx; Bumped plug @ 650 psi; Float held.

29.17'	1 Jt. 4-1/2" 10.50# J-55 ST&C Csg New
37.18'	Cut Jt. 4-1/2" 10.50# J-55 ST&C Csg New
3,442.78'	88 Jts 4-1/2" 10.50# J-55 ST&C Csg New
1.40'	Halliburton Float Collar
78.34'	2 Jts 4-1/2" 10.50# J-55 ST&C Csg New
.70'	Halliburton Float Shoe
3,595.57'	TOTAL

Cut Jt In 37.68', Out 1.50'

Csg Set @ 3,560.90' (Pulled up 6') Cmt'd w/350 sx ClC w/3% Lo-Dense & 1/4# Celloflake mixed @ 11.4#/gal, followed w/350 sx Class "C" w/6# Salt & 1/4# Celloflake mixed @ 14.8#/Gal. Bumped plug w/58 Bbls w/1000 psi @ 3:10 a.m. 7-14-77. Float held; Circ. particles of Celloflake; No Cement.

W.O.C. 20 1/2 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Guido Roach TITLE Production Clerk DATE 8-1-77

FOR RECORD ONLY

APPROVED BY W. A. S. S. S. S. TITLE MANAGER, DISTRICT II DATE AUG 3 1977

CONDITIONS OF APPROVAL, IF ANY: