

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
SEP 2 1977
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-187

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Gulf Oil Corporation

3. Address of Operator
P. O. Box 670, Hobbs, NM 88240

4. Location of Well
UNIT LETTER **C** **810** FEET FROM THE **North** LINE AND **1980** FEET FROM THE **West** LINE, SECTION **16** TOWNSHIP **23-S** RANGE **27-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3140' GL

7. Unit Agreement Name
8. Farm or Lease Name Eddy "GF" State
9. Well No. 1
10. Field and Pool, or Wildcat Undersouth Carlsbad Morrow
12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 9 1/2" hole to 8990', completed 4:00 PM 8-27-77. Ran 200 jts and 1 cut jt 8971' of 7 5/8" 29.70# & 26.40# N-80 & S-95 casing. Set at 8990'. Cemented with 400 sacks lite with .5% CFR-2 and 400 sacks Class H with .5% CFR-2. WOC over 24 hours. Tested casing with 3000# for 30 minutes - OK. Temperature Survey indicated top of cement at 4310'. Started drilling 6 1/2" hole at 8990' at 1:30 PM 8-30-77.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Norbon B. Sikes Jr. TITLE Area Engineer DATE 8-31-77

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: