

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLI
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 10895

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

North Horseshoe Bend Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat-Strawn

11. SEC., T., R., N., OR BLK. AND
SURVEY OR AREA

Sec. 22, T23S, R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Exxon Corporation

3. ADDRESS OF OPERATOR

P.O. Box 1600, Midland TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FNL and 1980' FEL of Sec. 22

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, BT, GR, etc.)

GR - 3857'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Class H cement to be used on all plugs

Establish injection rate into perfs, set retainer at 9600', test backside to 500 psi. Pump 100 sx to fill 5 1/2" from 9600'-10052' and sqz perfs. Sting out of retainer and spot 35' cmt on top of retainer.

Displace csg w/ salt gel to csg cut off point at 8010'.

Cut off csg at approximately 8010'.

Displace hole with salt gel.

Spot 50 sx from 8050'-7900'. WOC and tag.

Spot 40 sx from 5950'-5800'.

Spot 40 sx from 4600'-4450'.

Spot 50 sx from 2500'-2350' covering 9 5/8" csg shoe. WOC and tag.

Spot 220 sx from 600' to surf covering 16" csg shoe and filling 9 5/8" to surf.

Cut off wellhead and install dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

Stephen Johnson

TITLE

Administrative Specialist

DATE

04-27-88

(This space for Federal or State office use)

APPROVED BY

RESOURCES

TITLE

DATE

5-9-88

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side