

After PEA

EXXON COMPANY, U.S.A.
SOUTHWESTERN DIVISION

**PRODUCTION OPERATIONS
ENGINEERING**

DATE:

PAGE: OF

WELLBORE SKETCH AND WELL HISTORY

ELEV. KB above Cmt plug surf-
600w/220sxHole size 20"TOC Surf

SURFACE CASING:

16", 65', CSG @ 150'Cmt w/ 105 sx, circ sx
+ 3 yds 1st m xHole size 12 1/4"TOC Surf

Cmt plug 2350-2500w/50sx (TAG)

INTERMEDIATE CASING:

9 5/8", 36', K.S.S. SET @ 2395'Cmt w/ 1415 sx circ sx

Cap. 0773

4450 - 4600 w/40sx

5800 - 5950 w/49sx

Hole size 7 7/8"TOC 8010' (T.S.)

Cmt plug 7900-8050w/50sx (TAG)

Packer @ ± 9600

Ret @ 9600, 582w/100sx / 35' on top

9696 - 9704

9908 - 9928

9991 - 9995

10,032 - 10,052

Ret @ 10,860w/20' cmt on top

10,739 - 10,949 (582dw/100sx)

PRODUCTION CASING:

5 1/2", 17+20', N-50 SET 11500'Cmt w/ 925 sx, circ sx

Cap. 0232 Orif + 4.653 Yield 7036

TUBING DETAIL

Size Grade JTS SET @ BHA PUMP: RODS:

WELL HISTORY

TO: 11500' BBO.