

This form is to be filed with the appropriate District Office of the Commission not later than 90 days after the completion of any newly-drilled or deepened well. It shall be accompanied by a copy of all electrical and radio-activity logs run in the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of sectionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

### INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

#### Southeastern New Mexico

T. Anhy \_\_\_\_\_  
 T. Salt \_\_\_\_\_  
 B. Salt \_\_\_\_\_  
 T. Yates \_\_\_\_\_  
 T. 7 Rivers \_\_\_\_\_  
 T. Queen \_\_\_\_\_  
 T. Grayburg \_\_\_\_\_  
 T. San Andres \_\_\_\_\_  
 T. Glorieta \_\_\_\_\_  
 T. Paddock \_\_\_\_\_  
 T. Blinberry \_\_\_\_\_  
 T. Tubb \_\_\_\_\_  
 T. Drinkard \_\_\_\_\_  
 T. Abo \_\_\_\_\_  
 T. Wolfcamp \_\_\_\_\_  
 T. Penn. \_\_\_\_\_  
 T. Cisco (Bough C) \_\_\_\_\_

T. Canyon \_\_\_\_\_  
 T. Strawn 11,454  
 T. Atoka 11,530  
 T. Miss \_\_\_\_\_  
 T. Devonian \_\_\_\_\_  
 T. Silurian \_\_\_\_\_  
 T. Montoya \_\_\_\_\_  
 T. Simpson \_\_\_\_\_  
 T. McKee \_\_\_\_\_  
 T. Ellenburger \_\_\_\_\_  
 T. Gr. Wash \_\_\_\_\_  
 T. Granite \_\_\_\_\_  
 T. Delaware Sand 2,475  
 T. Bone Springs \_\_\_\_\_  
 T. Cherry Canyon 3,446  
 T. Morrow 12,250

#### Northwestern New Mexico

T. Ojo Alamo \_\_\_\_\_  
 T. Kirtland-Fruitland \_\_\_\_\_  
 T. Pictured Cliffs \_\_\_\_\_  
 T. Cliff House \_\_\_\_\_  
 T. Menefee \_\_\_\_\_  
 T. Point Lookout \_\_\_\_\_  
 T. Mancos \_\_\_\_\_  
 T. Gallup \_\_\_\_\_  
 Base Greenhorn \_\_\_\_\_  
 T. Dakota \_\_\_\_\_  
 T. Morrison \_\_\_\_\_  
 T. Todilto \_\_\_\_\_  
 T. Entrada \_\_\_\_\_  
 T. Wingate \_\_\_\_\_  
 T. Chinle \_\_\_\_\_  
 T. Permian \_\_\_\_\_  
 T. Penn. "A" \_\_\_\_\_

T. Penn. "B" \_\_\_\_\_  
 T. Penn. "C" \_\_\_\_\_  
 T. Penn. "D" \_\_\_\_\_  
 T. Leadville \_\_\_\_\_  
 T. Madison \_\_\_\_\_  
 T. Elbert \_\_\_\_\_  
 T. McCracken \_\_\_\_\_  
 T. Ignacio Qtzite \_\_\_\_\_  
 T. Granite \_\_\_\_\_

#### OIL OR GAS SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 6, from \_\_\_\_\_ to \_\_\_\_\_

#### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
 No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

#### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	370	370	Redbed				
370	825	455	Redbed & Anhy				
825	895	70	Anhy-Sand				
895	2475	1580	Anhy				
2475	3446	971	Sand - dolomite				
3446	5960	2514	Sand-shale-dolomite				
5960	7040	1080	Lime-shale				
7040	7570	530	Shale-lime				
7570	8850	1280	Lime & shale				
8850	9216	366	Sand				
9216	11,454	2238	Shale -Lime				
11,454	11,530	76	Lime				
11,530	12,250	720	Lime-sand-chert				
12,250	13,034	784	Lime-sand-chert				