	vorm C+10) Supersedex Old
DISTURBED DOD	C-102 and C-103
SAMEATC NEW MEXICO OIL CONSERVATION COMMISSION	Ellectivo 11-65
CALC REPEIVE	
U.S.G.S.	Sin Indicute Type of Leese State / Pee (X)
LAND OFFICE	······································
JUN 1 2 1978	a, State GH & Gas Lense Ro.
	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THE PARTICIPATION FOR FRANKLING CO.C.	
I. O'L X GAT DTHER.	7. Unit Agreenicat Non <del>g</del>
A forme of Operator	6. Farm of Lease Name
The Eastland Oil Company is	Harmoun Fod Com
1. A thees of C, senset	Harroun Fed. Com.
	1
704 Western United Life Building, Midland, Texas 79701	10. Field and Pool, or Wildon
	Undesignated Delaware
UNIT LETTES L 2310 FEET FACH THE SOUTH LINE AND 990 FEET FACH	
N 20 225 28E	
THE West THE SECTION 29 TOWNSHIP 22S RANGE 28E NORMEN.	AMANANANANANANANANANANANANANANANANANANA
WINTEN TO A State of the state	12. County
3035' GR	Eddy
76. Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
PERFERM REMEDIAL WORK	ALTERING CASING
TEMPERARILY ADANDOR	PLUG AND AGANDONMENT [X]
FULL ON ALTER CASING	
0THER	
6781 R	
17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1963.	estimated date of starting any proposed
Plugging operations were begun on March 12, 1978 and completed on	the same date.
Casing in the hole consisted of 352 feet of 8 5/8", 24#, J-55 cemented	with 250 sacks
class C, 2% CaCl <sub>2</sub> and cement circulated. No casing was recovered. An	8" cable
tool hole was drilled to 2477 feet and a 6" hole drilled to total depth	of 2540 feet
in the Delaware sand.	
Two inch tubing was run to 2508 feet and the hole loaded with 10.0#	/gal. salt mud.
Salt mud was used to displace plugs. Cement plugs were set as follows	using Halliburton
Services and Howco Class C cement:	
	•
35 sx from 2508' to 2400' (Top of Delaware sand)	
35 sx from 2200' to 2100' (Base of salt @ 2150')	
35 sx from 400' to 300' (In and out of surface casing)	
10 sx from 30' to surface.	
The location has been leveled and cleared of junk and a marker inst	alled at the
surface. The location is ready for inspection.	

id, I hereby certify that the information above is free and complete to the best of my knowledge and belief.

.

$\hat{\rho}$	,	
HUNTO These	Superintendent	GANE 6/6/78

.

TITLE\_

DATE \_\_\_

---- -

APPRCYCH AY