

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

APR 20 1978

O. C. C.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR REEQUIP A WELL IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-102) FOR SUCH PROPOSALS.

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
K-3077
7. Unit Agreement Name
8. Farm or Lease Name
Terra State
9. Well No.
3
10. Field and Pool, or Wildcat
Yarrow Delaware
12. County
Eddy

1. OIL ☐ GAS ☒ OTHER ☐
2. Name of Operator
J. M. Huber Corporation
3. Address of Operator
1900 Wilco Building, Midland, Texas 79701
4. Location of Well
UNIT LETTER N 1096 FEET FROM THE South LINE AND 1554' FEET FROM
West 15 TOWNSHIP 23-S RANGE 26-E NMPN.

15. Elevation (Show whether DF, RT, GR, etc.)
3321 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/8/78 Drilling @ 1150', slope 2-3/4 deg. @ 618', 2-1/2 deg. @ 724', 2-3/4 deg. @ 819', 5 deg. @ 913', 5 deg. @ 9750', 4-3/4 deg. @ 1070', Mud wt. 9.8#, viscosity 28.

3/9/78 Drlg. @ 1680', slope 3 deg. @ 1384', 2-1/4 deg. @ 1666'. Mud Wt. 9.8#

3/10/78 Drlg. @ 2080', slope 2-1/4 deg. @ 1731', 2-1/4 deg. @ 1979', Mud Wt. 10.2#, viscosity 33, Mix 50 sks. Polymer brine mud, 5 gals. LD 8, 8 sks. soda ash, 3 sks. caustic, 3 loads brine water, 1 load fresh water

3/11/78 Drlg. @ 2500', slope 1-1/4 deg. @ 2295'. Mud wt. 10.1#, viscosity 36, water loss 3.8 cc's, Ph 10. Mix 10 sks. Polymer mud, 5 sks. paper, 3 sks. caustic & 10 gals. defoamer.

3/12/78 Drlg. @ 2795', slope 1-1/4 deg. @ 2706'. Mud wt. 10.2#, viscosity 37, water loss 4 cc's, Ph 8. Mix 15 sks. Polymer mud & 3 sks. soda ash.

3/13/78 Drlg. @ 3275', slope 1-1/2 deg. @ 2984', 1/2 deg. @ 3234'. Mud wt. 10.1#, viscosity 34, water loss 4.2 cc's, Ph. 8. Mix 5 sks. Polymer

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	TITLE	DATE
Robert G. Setzler	Dist. Prod. Mgr.	April 17, 1978
APPROVED BY	TITLE	DATE
W. G. Gressett	SUPERVISOR, DISTRICT II	MAY 4 1978
CONDITIONS OF APPROVAL, IF ANY:		