

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 4 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Amoco Production Company ✓

3. Address of Operator
P. O. Drawer A, Levelland, Texas 79336

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 26 TOWNSHIP 23-S RANGE 28-E NMPL.

15. Elevation (Show whether DF, RT, GR, etc.)
3012.4 GR

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

6. Farm or Lease Name
Pardue Farms Gas Com

9. Well No.
1

10. Field and Pool, or Wildcat
Wildcat - Morrow

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MGF Drilling Co. Rig No. 22 spudded a 20" hole at 3:30 A.M. 3-14-78. Reached TD of 408' on 3-16-78. Ran 16" 65# H-40 ST&C casing set at 408'. Cement with 500 sx Class C cement + 2% CACL. Plugged down 4:30 P.M. 3-16-78. Circulated 40 sx to surface. WOC 18½ hrs. Test casing with 600# for 30 minutes. Test ok. Reduced hole to 14-3/4" and resumed drilling.

Reached TD of 3025' 3-25-78. Ran 10-3/4" 45.5/40.5* K-55 ST&C casing and set at 3025'. Cement with 1730 sx Howcolite + 5# Gilsonite + 1/4# Flocele + 8# Salt/sx followed by 200 sx Class C + 2% CACL. Plugged down 3:15 P.M. 3-25-78. Cement did not circulate. Ran temp. survey and found top of cement at 220'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Randy Atkins TITLE Asst. Administrative Analyst DATE 3-29-78

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE APR - 5 1978

CONDITIONS OF APPROVAL, IF ANY:

0 + 4 - NMOCC, A, 1-Div, 1-Susp, 1-RC