



PACER INSTALLATION PLAN

CB-488

REPAIRED FOR		DATE					
Joe Mitchell Amoco		6-14-93					
LEASE	WELL NO.	FIELD	CO./PARISH	STATE	☐ NEW COMPLETION ☐ WORKOVER		
Purdue Farm	GMS CORP		Eddy	N. Mex			
INSTALLATION	ITEM	LENGTH	FROM	TO	DESCRIPTION	OD	ID
		17.00'	Ø	17.00'	K.B.		
	1	11,364.49	17.00'	11,381.47	366.57 2 3/8 N-80 TBG.		
Top Liner							
11,066	2	2.67	11,381.47	11,384.14	2 3/8 G.L. sliding sleeve w/ 1.875	3.063	1.87
11,484	3	1191.44	11,384.14	12,575.58	2 3/8 TBG N-80 39.575		
11,798	4	1.97	12,575.58	12,577.55	5" 2 3/8 ON/OFF TOOL w/ 1.875 F PROFILE	3.750	1.82
	5	7.08	12,577.55	12,584.63	5"-15-18" X 2 3/8 IN. IT PKR.	4.125	1.93
	6	31.30	12,584.63	12,615.93	1 57 2 3/8 N-80 TBG		
	7	.85	12,615.93	12,616.78	2 3/8 F-Nipple w/ 1.81 PROFILE	3.063	1.81
	8	4.37	12,616.78	12,621.15	2 3/8 mule shoe guide		
			12,621.15		Top Liner 5"-12.93" OD 11,077		
GENERAL REMARKS					RETRIEVING METHOD—INCLUDE SHEAR RELEASE VALUE OR COLLET SNAP OUT VALUE		
PKR set w/ 15,000 compression					TOP PACKER: 12,577.55		
To shift sliding sleeve open -up					MIDDLE PACKER: 12,581.09		
To close -down					LOWER PACKER: 12,584.63		
COMPLETION FLUID TYPE AND WEIGHT							
270 K.C.I. w/ PKR Fluid							
AREA	OPERATOR'S NAME		DATE		DELIVERY TICKET NUMBER		
Hobby, N. M.	Billy J. Price		6-15-93				