

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

APR 14 1978

O. C. D.
ARTESIAN OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
GULF OIL CORPORATION

Address of Operator
P. O. Box 670, Hobbs, NM 88240

Location of Well
UNIT LETTER **G** **1880** FEET FROM THE **North** LINE AND **1980** FEET FROM
THE **East** LINE, SECTION **28** TOWNSHIP **23-S** RANGE **26-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3325' GL

50. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-776

7. Unit Agreement Name

6. Farm or Lease Name
Eddy "GN" State Com

9. Well No.
1

10. Field and Pool, or Wildcat
Undes S. Carlsbad Morro

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPS. ☒
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☒
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

McVay Drilling co spudded a 20" hole at 10 AM 4-8-78. Reached TD of 20" hole at 300' at 6:30 PM 4-8-78. Ran 7 jts and 1 cut jt 16" 65# H-40 ST & C (286') Set at 290'. Cemented with 150 sackd RFC with 1% CaCl2, 2% D-53, 135 sacks 50-50 poz 4% D-20, 2% CaCl2, 200 sacks Class C with 4% CaCl2. Cement did not circulate. Go in hole with 1" pipe to 265', cement with 50 sacks Class C with 2% CaCl2, 236', cement with 50 sacks Class C with 2% CaCl2; 191' cement with 170 sacks Class C with 4% CaCl2; 60' cement with 130 sacks Class C with 4% CaCl2. Cement circulated. WOC 18 hours. Tested 16" casing to 200# for 30 min ok.

Started drilling a 13 3/4" hole at 11 AM 4-10-78 at 300'.

I, hereby certify that the information above is true and complete to the best of my knowledge and belief.

CREATED BY N. B. Sikes, Jr. TITLE Area Engineer DATE 4-11-78

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE APR 18 1978

CONDITIONS OF APPROVAL, IF ANY: