

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUN 12 1978

SUNDARY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR PLUG BACK TO A DIFFERENT RESERVOIR.
(USE APPLICATION FOR PERMIT TO DRILL OR TO REPER OR PLUG BACK TO A DIFFERENT RESERVOIR.)

O. E. E.
ARTESIA, OFFICE

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-

2. Name of Operator
The Eastland Oil Company

3. Address of Operator
704 Western United Life Building, Midland, Texas 79701

4. Location of Well
UNIT LETTER **A** **330** FEET FROM THE **North** LINE AND **976** FEET FROM
THE **East** LINE, SECTION **32** TOWNSHIP **22S** RANGE **28E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3012' GR

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

6. Farm or Lease Name
Harroun "A"

9. Well No.
2

10. Field and Pool, or Wildcat
Undesignated Delaware

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Drilled to total depth of 2476' in sand with a 8" cable tool hole on May 27, 1978. After running logs, ran 64 joints 4 1/2", 9.5#, J-55 casing with Halliburton packer shoe set at 2465'. Cemented with 200 sacks Class C - pozmix, 2% gel and 300 sacks Lite with 6# salt/sack. Circulated out 25 sacks excess cement. Cement was in place at 2:00 p.m., May 28, 1978.

Allowed cement to set 42 hours and swabbed and bailed 4 1/2" casing dry. After standing for one hour, casing was bailed with no fluid entry. Drilled packer shoe and cleaned to total depth at 8:00 p.m., May 30.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: George P. Neal TITLE: Superintendent DATE: 6/6/78

APPROVED BY: W. A. Gressett TITLE: SUPERVISOR, DISTRICT II DATE: JUN 13 1978

CONDITIONS OF APPROVAL, IF ANY: