

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than _____ days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____ T. Canyon 9290
T. Salt _____ T. Strawn 10,870
T. Salt _____ T. Atoka _____
T. Yates _____ T. Miss _____
T. 7 Rivers _____ T. Devonian _____
T. Queen _____ T. Silurian _____
T. Grayburg _____ T. Montoya _____
T. San Andres _____ T. Simpson _____
T. Glorieta _____ T. McKee _____
T. Paddock _____ T. Ellenburger _____
T. Blinberry _____ T. Gr. Wash _____
T. Tubb _____ T. Granite _____
T. Drinkard _____ T. Delaware Sand 2180
T. Abo _____ T. Bone Springs 5588
T. Wolfcamp 9032 T. Third Bone Springs
T. Penn. 9895 T. 8620
T. Cisco (Bough C) _____ T. _____

Northwestern New Mexico

T. Ojo Alamo _____ T. Penn. "B" _____
T. Kirtland-Fruitland _____ T. Penn. "C" _____
T. Pictured Cliffs _____ T. Penn. "D" _____
T. Cliff House _____ T. Leadville _____
T. Menefee _____ T. Madison _____
T. Point Lookout _____ T. Elbert _____
T. Mancos _____ T. McCracken _____
T. Gallup _____ T. Ignacio Qtzite _____
T. Base Greenhorn _____ T. Granite _____
T. Dakota _____ T. Morrow Clastic 11,688
T. Morrison _____ T. Chester 12,233
T. Todilto _____ T. _____
T. Entrada _____ T. _____
T. Wingate _____ T. _____
T. Chinle _____ T. _____
T. Permian _____ T. _____
T. Penn. "A" _____ T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 11,923 to 11,966 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole. Regular water basin sand and gravel.

No. 1, from 50 to 240 feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	240	240	sand & gravel	7116	7320	204	sandstone w/ shale stringers
240	340	100	red bed	7320	8620	1300	limestone & shale stringer
340	620	280	gyp & salt	8620	9032	412	sandstone
620	1120	500	anhydrite	9032	9290	258	limestone w/shale stringer
1120	1363	243	salt	9290	9700	410	shale w/lime stringers
1363	1475	112	anhydrite	9700	9895	195	limestone w/shale stringers
1475	1850	375	salt	9895	10290	395	limestone
1850	2080	230	anhydrite	10290	10810	580	limestone w/shale stringers
2080	2110	30	delaware (lamar shale)	10870	11688	818	strawn limestone
2110	2180	70	limestone	11688	12233	545	sandstone w/shale stringers
2180	5588	3408	sandstone, shale & lime breaks	12233	12350	117	limestone w/shale stringers
5588	6606	1018	limestone				
6606	6810	204	shale & sandstone				
6810	7116	306	limestone				