

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

|  |   |                      |   |                    |                       |
|--|---|----------------------|---|--------------------|-----------------------|
| Operator <u>PRYMIAN DRILLING Sales &amp; Service</u> |   | Lease <u>Ergenie</u> |   | Well # <u>1</u>    |                       |
| Location of Well                                     | Unit <sup>M</sup><br><u>945 S</u><br><u>641-W</u> | Section<br><u>17</u> | Township<br><u>22</u>                   | Range<br><u>27</u> | County<br><u>Eddy</u> |
| Drilling Contractor                                  |   |                      | Type of Equipment<br><u>Cable Tools</u> |                    |                       |

APPROVED CASING PROGRAM

| Size of Hole  | Size of Casing | Weight Per Foot | New or Used | Depth      | Sacks Cement     |
|---------------|----------------|-----------------|-------------|------------|------------------|
| <u>12 3/4</u> | <u>10 3/4</u>  | <u>54</u>       | <u>335</u>  | <u>335</u> | <u>Circulate</u> |
| * <u>8</u>    | <u>7</u>       | <u>32</u>       |             | <u>453</u> | <u>Circulate</u> |
|               |                |                 |             |            |                  |

Casing Data:

Production Surface joints of   inch #   Grade    
(Approved) (Rejected)

Inspected by   date  

Cementing Program

Size of hole 8" Size of Casing 7" Sacks cement required 135

Type of Shoe used Texas Float collar used NO Btm 3 jts welded Yes

TD of hole 592 Set 453 Feet of 7 Inch 32 # Grade K-55

-used csg. @ 453 with 135 sacks neat cement around shoe

+   sax   additives 3% Calcium Chloride

Plug down @ 6:10 (AM) (PM) Date 6-28-78

Cement circulated Yes No. of Sacks 20

Cemented by Byron Jackson Witnessed by B.W. Weaver

Temp. Survey ran @   (AM) (PM) Date   top cement @  

Casing test @   (AM) (PM) Date  

Method Used   Witnessed by  

Checked for shut off @   (AM) (PM) Date  

Method used   Witnessed by  

Remarks: